

*High-quality, full-grain semi-aniline leather with natural grain
and velvety soft feel*

Technical Data

Range of application	Furniture, objects, shoes, leather goods of all kind		
Raw material	South-German and Austrian cattle hides		
Tanning / Production	Mineral tanning		
Dyeing	Dyed in drums with high-quality dyes		
Finishing	non solvent PU-finishing		
Leather type	Semianiline		
Colors on stock	111 (according to color card)		
Order quantity	starting with 1 hide from our stock program		
Special- / Customer's colors	Minimum order quantity of 50 hides		
Delivery conditions	ex works Großbottwar		
Thickness	1.0 - 1.2 mm		
Average size	5.6 m ²		
Selection	SPSO		
Light fastness	DIN EN ISO 105-B02	≥ 5	
Tear strength	DIN EN ISO 3377-1	≥ 20 N/mm	
Permanent folding behaviour	DIN EN ISO 5402-1	20,000 flexes	
Rubbing strength	DIN EN ISO 11640		
	dry	500 cycles	≥ 4
	wet	80 cycles	≥ 3 - 4
	perspiration	50 cycles	≥ 3 - 4
pH-value	DIN EN ISO 4045	> 3.5	
Adhesion of finish	DIN EN ISO 11644 / IUF 470	≥ 2 N/10mm	
Fire behaviour	The article fulfills several fire behaviours. Please contact us for further information.		
Treatment / Care	Wipe once a month with a clean, slightly damp cloth. If necessary, only use special cleaner made by LCK.		
Notes	The PCP-content and AZO-dyes of all our leathers comply with the actually valid provisions concerning the by-law chemical prohibition, clause 15, respectively the utensils regulation of the Federal Republic of Germany.		
	Again we authenticate that chromium 6 is unverifiable in our leather.		
	The limit of 5mg PCP/kg won't be overstepped.		

*Micro-pigmented thick aniline leather with natural grain
and velvet-like soft touch.*

Technical Data

Range of application	Furniture, objects, shoes, leather goods of all kind		
Raw material	South-German and Austrian cattle hides		
Tanning / Production	Mineral tanning		
Dyeing	Dyed in drums with high-quality dyes		
Finishing	non solvent PU-finishing		
Leather type	Protected Aniline		
Colors on stock	40 (according to color card)		
Order quantity	starting with 1 hide from our stock program		
Special- / Customer's colors	Minimum order quantity of 40 hides		
Delivery conditions	ex works Großbottwar		
Thickness	1.4 - 1.6 mm		
Average size	5.6 m ²		
Light fastness	DIN EN ISO 105-B02	≥ 3	
Tear strength	DIN EN ISO 3377-1	≥ 20 N/mm	
Permanent folding behaviour	DIN EN ISO 5402-1	20,000 flexes	
Rubbing strength	DIN EN ISO 11640		
	dry	50 cycles	≥ 3
	wet	20 cycles	≥ 3
	perspiration	20 cycles	≥ 3
pH-value	DIN EN ISO 4045	> 3.5	
Adhesion of finish	DIN EN ISO 11644 / IUF 470	≥ 2.5 N/10mm	
Fire behaviour	The article fulfills several fire behaviours. Please contact us for further information.		
Treatment / Care	Wipe once a month with a clean, slightly damp cloth. If necessary, only use special cleaner made by LCK.		
Notes	The PCP-content and AZO-dyes of all our leathers comply with the actually valid provisions concerning the by-law chemical prohibition, clause 15, respectively the utensils regulation of the Federal Republic of Germany.		
	Again we authenticate that chromium 6 is unverifiable in our leather.		
	The limit of 5mg PCP/kg won't be overstepped.		

Natural vintage leather with waxed surface, unique deep look and warmth.

Technical Data

Range of application	Furniture, objects, shoes, leather goods of all kind		
Raw material	South-German and Austrian cattle hides		
Tanning / Production	Mineral tanning		
Dyeing	Dyed in drums with high-quality dyes		
Finishing	non solvent PU-finishing		
Leather type	waxed Aniline		
Colors on stock	8 (according to color card)		
Order quantity	starting with 1 hide from our stock program		
Special- / Customer's colors	Minimum order quantity of 40 hides		
Delivery conditions	ex works Großbottwar		
Thickness	1.4 - 1.6 mm		
Average size	5.6 m ²		
Light fastness	DIN EN ISO 105-B02	≥ 3	
Tear strength	DIN EN ISO 3377-1	≥ 20 N/mm	
Rubbing strength	DIN EN ISO 11640		
	dry	50 cycles	≥ 3
	wet	20 cycles	≥ 3
	perspiration	20 cycles	≥ 3
pH-value	DIN EN ISO 4045	> 3.5	
Adhesion of finish	DIN EN ISO 11644 / IUF 470	≥ 2.5 N/10mm	
Fire behaviour	The article fulfills several fire behaviours. Please contact us for further information.		
Treatment / Care	Wipe once a month with a clean, slightly damp cloth. If necessary, only use special cleaner made by LCK.		
Notes	The PCP-content and AZO-dyes of all our leathers comply with the actually valid provisions concerning the by-law chemical prohibition, clause 15, respectively the utensils regulation of the Federal Republic of Germany. Again we authenticate that chromium 6 is unverifiable in our leather. The limit of 5mg PCP/kg won't be overstepped.		

*Natural vintage leather with velvety soft surface.
Over time, patina and traces of use will give the leather an unique appearance.*

Technical Data

Range of application	Furniture, objects, shoes, leather goods of all kind		
Raw material	South-German and Austrian cattle hides		
Tanning / Production	Mineral tanning		
Dyeing	Dyed in drums with high-quality dyes		
Leather type	Aniline, slightly polished		
Colors on stock	10 colors (dated 2021)		
Order quantity	starting with 1 hide from our stock program		
Special- / Customer's colors	Minimum order quantity of 50 hides		
Delivery conditions	ex works Großbottwar		
Thickness	1.0 - 1.2 mm		
Average size	5.5 m ²		
Light fastness	DIN EN ISO 105-B02	≥ 3	
Tear strength	DIN EN ISO 3377-1	≥ 20 N/mm	
Rubbing strength	DIN EN ISO 11640		
	dry	50 cycles	≥ 3
	wet	20 cycles	≥ 3
	perspiration	20 cycles	≥ 3
	at color black ≥ 2		
pH-value	DIN EN ISO 4045	> 3.5	
Fire behaviour	The article fulfills several fire behaviours. Please contact us for further information.		
Treatment / Care	Wipe once a month with a clean, slightly damp cloth. If necessary, only use special cleaner made by LCK.		
Notes	The PCP-content and AZO-dyes of all our leathers comply with the actually valid provisions concerning the by-law chemical prohibition, clause 15, respectively the utensils regulation of the Federal Republic of Germany.		
	Again we authenticate that chromium 6 is unverifiable in our leather.		
	The limit of 5mg PCP/kg won't be overstepped.		