

PRODUCT INFORMATION

Forest and Garden Equipment



Forstprotect

BIO Chainsaw Oil "Blue Engel"

DESCRIPTION

REKTOL Forstprotect with „Blue Angel“ approval, practice-proven chainsaw oil, based on renewable natural resource rape oil, provides high viscosity of ISO VG 100. Special additives protect the product against premature ageing, resin deposits and improves adhesive and sliding properties. Forstprotect is suitable for reliable lubrication of faster engine and electric saw units, used for all types of wood. An optimum lubrication is guaranteed, also at low operation temperatures.

The product may not be mixed with synthesis or mineral oil.

Rektol BIO-Saw Chain Oil Forstprotect complies with the Ecolabel criteria „Blauer Engel“ (RAL-UZ 178), as the share of renewable natural resource according to DIN CEN/TS 16137 (DIN SPEC 91236) ca. 95%.

Forstprotect can be stored for at least 4 years.



www.blauer-engel.de/uz178

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,922	g/ml
Flashpoint	DIN ISO 2592	230	°C
Viscosity at 40 °C	DIN 51562	100	mm ² /sec
Colour		green	

PRODUCT INFORMATION

Forest and Garden Equipment



AVAILABLE PACKAGING



1L



5L



20L



60L



205L

Artikel-Nr. 518000011 518000016 518000020 518000030 518000036

The information in this product data sheet is based on over 130 years of experience of the company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend consulting our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.