

# Solidbase SK 2 mm: 8 x 1 m (8 m<sup>2</sup>)

Art. nr - 681371

**estillon**  
WE WILL IMPROVE YOUR FLOOR

Scan this QR code to view this product on our website.



## Description

Solidbase SK 2 mm is a premium heavy underlayment that boasts a compressive strength of over 400 kPa. Made from a combination of PU and mineral fillers, it features a self-adhesive surface on one side, allowing for quick installation. It is perfectly suited for both residential and project use with LVT dryback flooring. Additionally, it effectively isolates impact and walking noise.

# Solidbase SK 2 mm: 8 x 1 m (8 m<sup>2</sup>)

Art. nr - 681371

## Specifications

Floor type	LVT Dryback
Product weight	2000 g/m <sup>2</sup>
Product dimensions (Length)	8 m
Product dimensions (Width)	1 m
Product dimensions in m2	8 m <sup>2</sup>
Base unit	Roll
Thickness	2 mm
Density	1000 kg/m <sup>3</sup>
Material	Middle layer: PU / mineral composition Bottom layer: Self-adhesive layer
Brand	Solidbase
TOG rating	0.1 TOG
Thermal resistance - R-value	0.01 m <sup>2</sup> K/W
Suitable for underfloor heating	Yes
Suitable for floor cooling	Yes
SD (Steam Diffusion)	>75 micron
PC (Punctual Conformability)	~ 0.79 mm
CS	CS3
CS/CC (compressive Strength / Compressive Creep)	>450 kPa
Domestic use	Yes

# Solidbase SK 2 mm: 8 x 1 m (8 m<sup>2</sup>)

Art. nr - 681371

Project use	Yes
Laying method	Floating
DIBT certificate	Z-158.10-50
Green choice label	Yes
Type of base floor	Wooden floor / Fixed sand cement floor / Floating screed
Sound-reducing - $\Delta Lw$	16 dB $\Delta Lw$
Flame-retardant	Bfl-S1
Flame-retardant - Test method	EN ISO 9239-1: 2010
RWS (Radiated Walking Sound (reduction))	up to 7 %
RWS (Radiated Walking Sound (reduction)) - Test Method	EPLF WD 021029-5
RLB (Resistance to Large Ball)	~ 800 mm
DL (Dynamic Load)	> 3,000,000 cycles
CS/CC (Compressive Strength / Compressive Creep)	>450 kPa

# Solidbase SK 2 mm: 8 x 1 m (8 m<sup>2</sup>)

Art. nr - 681371

**estillon**  
WE WILL IMPROVE YOUR FLOOR

