



Rely on us.SM

Premotherm BE 2600

DE-UZ 237 certified printing ink for Heatset web offset printing

Process colour series for use on MC,LWC up to SC papers

Product Features

- Complies with ISO 2846-1 colour standard for four colour printing.
- Rheological characteristics (medium to high tack and viscosity) are set for use on MC/LWC to SC papers.
- De-inking test results in compliance with DE-UZ 237 criteria (minimal paper weight: 42.5 g/m²)
- DE-UZ 237 certified ink series

Advantages of Premotherm BE 2600 serie

- Suitable for printing with or without Isopropyl alcohol.
- Excellent performance characteristics.

FlintGroup

Premotherm BE 2600

	Printing properties							Printed materials						
	Dot gain	Gloss	Rub resistance	Drying	Press performance	Piling	Misting	NP	INP	SC-B	SC-A	MFC	LWC	MWC Matt
Premotherm BE 2600 series	++	+++	++	++	+++	+++	++	x	x	✓	✓	✓	✓	✓
+ Good ++ Very good +++ Excellent														
Printing properties mainly depend on the different paper qualities, machine settings and fount type.														

For optimum ink-transfer

Maintain the inking roller temperature between 27 °C - 33 °C.

Fountain solutions

We recommend HSF 9232 (hard water HSF 9232 (250)) for Manroland and KBA presses. Sunday Fount for Goss presses. For older and slower presses we recommend AF Superspeed.

Storage

For best pump ability the inks should be stored at minimum temperature of 20 °C - 25 °C.

More products. Streamlined access. Greater results.

Flint Group’s Print Media division offers a uniquely powerful combination of products, services and expertise; giving you access to the industry’s broadest range of pressroom products.

Inks and Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.



Flint Group
 Flint CPS Inks Netherlands B.V.
 Einsteinstraat 3
 2691 GV 's-Gravenzande
 The Netherlands
 www.flintgrp.com

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability.

Product names followed by ® are trademarks registered by Flint Group Incorporated.