

## Technical Data Sheet

Product Name: General purpose plastering mortar

Feature: Comply with Blue Angel Label DE-UZ 198  
Low emission  
No formaldehyde

Scope: Wall and ceiling for interior surface.

Composition: natural ore ,inorganic binder,auxiliaries



Specification : 20KG(GHS05,GHS07)

### Precautionary statement:

P261 Avoid breathing dust.

P264 Wash hands and face thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

P305+P351+P338+P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/ regional/ national/ international regulation

Application: 1.2kg dry mortar/m<sup>2</sup>/ mm thickness

Mortar preparation:

- 1)Add 30% weight water into mortar(mortar:water=1:0.3)
- 2)Mixing evenly
- 3)Using the trowel to apply mortar to the prepared substrate.

Construction temperature: Above 10 °C

Construction method: Scraping

Post treatment: Fresh mortar must prevent rain form erosion during hardening.

Caution :

- 1)The base wall should be solid and smooth.
- 2)The base wall should be kept dry.

3) For the wall with poor evenness, it should be divided into several scraps.

Safety instructions:

- 1) Stored in places where children can't reach them.
- 2) Ensure thorough ventilation during processing and drying.
- 3) Do not eat, drink or smoke when handling the plaster.
- 4) Clean tools with plenty of water and soap immediately after use.
- 5) Only pass on empty containers for recycling. Dried product residues can be disposed of as household waste.
- 6) Wear protective gloves and goggles.
- 7) Wear long trousers.
- 8) If plaster comes into contact with your eyes, immediately rinse them with lots of water and consult an ophthalmologist.
- 9) The affected parts of skin should be washed with plenty of water immediately.
- 10) The longer fresh plaster remains on your skin the greater the risk of severe skin damage.
- 11) Do not allow to enter drains, water bodies, ground or soil.
- 12) The manufacturer's occupational health and safety instructions must be followed in the processing stage.
- 13) Safety and safety precautions and safety data sheets on containers must be observed.
- 14) Keep children away from fresh plaster.

Storage

- 1) Keep dry when storing.
- 2) The maximum storage period is 12 months.
- 3) Use the container as soon as possible after opening it.