HP LASERJET MFP M140W (7MD72F)



Blue Angel User Information DE-UZ 219

The HP printing system HP LaserJet MFP M140w (7MD72F) is awarded with the environmental label Blue Angel (DE-UZ 219, edition January 2021) in Germany, for meeting altogether more than 100 strict certification criteria. Please note that the HP printing system HP LaserJet MFP M140w (7MD72F) is also suited for private use by end-consumers. In the following, essential environmental information on the device is summarised. Comprehensive information on the Blue Angel product requirements and detailed product specifications are available at www.blauer-engel.de.



PRINTING PAPER

This device is suitable for using recycled paper in accordance with EN 12281.

DOUBLE SIDED PRINTING/COPYING IN DELIVERY STATUS

A software supports the device to print/copy double-sided. Furthermore, the device features the capability to printout several pages of a digital file on one single page.

PRINT/COPY SPEED

20 pages per minute using normal mode (delivery setting).

LONGEVITY

- HP recommends a monthly page volume of up to 1000 pages for this device.
- All necessary exchange parts are available to the private user and can be replaced by him-/herself.
- Spare parts and exchange parts for the repair of this device model are still available at least five years after end of production.
- HP recommends following the intervals for cleaning and maintenance as described in the product information.

INFORMATION ON POST-CONSUMER RECYCLED PLASTIC

HP contributes to the conservation of resources by using post-consumer recycled plastic for production of new HP products. These plastics are recycled waste plastics stemming from private or commercial end-consumers. This HP device contains 0.21% of post-consumer recycled plastic.

RETURN OF EQUIPMENT

HP offers customers in Germany the opportunity to return used equipment. Information on the return of equipment is available at your local HP sales or customer-service centre or at http://www.hp.com/recycle.

RETURN OF CONSUMABLES

In Germany and many other countries, HP toner cartridges for this device can be returned cost-free to HP as part of the return and recycling programme. The packaging of each new HP toner cartridge contains information on how to participate in this programme. Or visit our website: http://www.hp.com/recycle.

22 February 2022, V01 1 of 3

YIELDS OF CONSUMABLES

The HP toner cartridge HP 141A (W1410A) shipped with the product has a reference yield of 950 pages, determined according to ISO/IEC standard 19752.

Further information can be found at http://www8.hp.com/h71041/learn-about-supplies/us/en/overview.php.

INFORMATION ON HANDLING OF THE TONER MODULES

- Please leave HP toner cartridges in their despatch packaging until you need them for use in your printer; when inserting the HP toner cartridge, please follow the information on handling.
- HP toner cartridges should never be opened by force. If toner dust escapes, e.g. as a result
 of inappropriate handling, inhalation of dust and skin contact are to be avoided as a
 precautionary measure.
- In case of skin contact wash affected areas thoroughly with soap and cold water. HP toner cartridges are to be kept out of the reach of children.

AIR EMISSIONS

With original HP toners, the device passes the air emission test for monochrome printing according to DE-UZ 219. Since plastics of new electrical devices generally release small amounts of volatile substances into the room air, we recommend providing sufficient air exchange in rooms where new devices are set up.

NOISE EMISSIONS

Declared sound power level for one-sided printing (Lwac) In monochrome print mode 20 pages/minute:

6.46 Bels and 64.6 Db

ENERGY

Energy information on HP LaserJet MFP M140w (7MD72E)

The consumption of electric power depends on its properties and on the way it is used. HP LaserJet MFP M140w (7MD72F) is designed and pre-set in a way to allow you to reduce electricity costs.

Directly after the last print or copy job, HP LaserJet MFP M140w (7MD72F) with its instant-on fuser technology switches over to an electric power saving mode, from which it can quickly print or copy again.

The device is so designed as to ensure that it can be switched to the Off-mode (standby) by pressing the on/off switch up to twice a day without suffering damage. This device does not have a switch by which it can be completely disconnected from the mains. When after having switched off the device you pull out the power plug, electric power consumption is completely stopped.

The table below lists the individual power consumption values as well as delay and recovery times (factory setting). With these values the device meets the Blue Angel requirements.

22 February 2022, V01 2 of 3

Overview of HP LaserJet MFP M140w (7MD72F) operating modes

Page throughput for A4 paper size (according to ISO/IEC 24734):

In monochrome print mode: 20 pages/minute with a resolution of 236x236dpcm (600x600 dpi) In monochrome copy mode: 20 pages/minute with a resolution of 236x236dpcm (600x600 dpi) (dpcm = dots per centimetre [Bildpunkte pro Zentimeter]); (dpi = dots per inch [Bildpunkte pro Zoll])

Switch symbol	Operation mode ¹	Power consumption ² watts	Delay time ³ minutes	Recovery time seconds
Maximum power consumption (switch-on): 764 watts				
	Printing (continuous operation at 20 pages/minute), monochrome	372	immediately	immediately
	Ready	2.8	immediately	immediately
	Sleep	1.1	1.2 (160)	2
	Off-mode (standby)	0.1	switch activated	-
	Disconnection from mains	0	e.g. pull out power plug	-

After the last print or copy job, the device switches over to electric power saving modes in several steps. By and by, electric power consumption is reduced in these modes. The device will switch over to the Ready mode first. Then the device switches over to Sleep mode after the delay time stated above.

Typical electricity consumption (TEC) of HP LaserJet MFP M140w (7MD72F)

Measured with Blue Angel energy settings enabled, as stated in the table above. The typical electricity consumption (TEC) of HP LaserJet MFP M140w (7MD72F) is 0.26 kWh/week.

TEC determined according to standard use cycle (per ENERGY STAR version 3.0), based on typical workplace dynamics (8 hours on each of the 5 workdays of a calendar week; 200 pages printed per workday). Energy testing follows ENERGY STAR 3.0 protocol with the following Blue Angel specifics: A4 format paper and line voltage of 230V. For the standard use cycle according to ENERGY STAR version 3.0 for this device, the following values were used: 20 print jobs per working day, each with 10 pages, single-sided at monochrome printing (200 pages/day).



² Averaged value, measured without accessories.

Delay time is the time that elapses after the end of the printing or copying process until the device enters the respective mode. The figures in brackets indicate the user-selectable range within which delay times can be adjusted. The delay time values apply to all primary functions of the device: printing, copying.