Samsung CLX-6260FR

Blue Angel User Information RAL-UZ 205



Nur für Deutschland – only for Germany – uniquement pour l'Allemagne – solo per la Germania

The printing system Samsung CLX-6260FR is awarded with the environmental label Blue Angel (RAL-UZ 205, edition January 2017) in Germany, for meeting altogether more than 100 strict certification criteria. Please note that the printing system Samsung CLX-6260FR is also suited for private use by end-consumers. In the following, essential environmental information on the device is summarised. Comprehensive information on the Blue Angel product requirements and detailed product specifications are available at www.blauer-engel.de.

Printing paper

This device is suitable for using recycled paper in accordance with EN 12281.

Double sided printing/copying in delivery status

The device is equipped with an automatic duplexer for double-sided printing and copying. Duplex printing is the default setting. Furthermore, the device features the capability to printout several pages of a digital file on one single page.

Longevity

- HP recommends a monthly page volume of up to 2,400 pages for this device.
- All necessary exchange parts are available to the private user and can be replaced by him-/herself.
- Spare parts and exchange parts for the repair of this device model are still available at least five years after end of production.
- HP recommends following the intervals for cleaning and maintenance as described in the product information.

Information on post-consumer recycled plastic

HP contributes to the conservation of resources by using post-consumer recycled plastic for production of new HP products. These plastics are recycled waste plastics stemming from private or commercial end-consumers. This HP device contains 0-1% of post-consumer recycled plastic.

Return of equipment

HP offers customers in Germany the opportunity to return used equipment. Information on the return of equipment is available at your local HP sales or customer-service centre or at http://www.hp.com/recycle.

Return of photoconductor drum

Photoconductor drums can be returned cost-free to HP just as the HP LaserJet toner cartridges for this device.

12 December 2017 / V1 1 of 3

Return of consumables

In Germany and many other countries, HP toner cartridges for this device can be returned cost-free to HP as part of the return and recycling programme. The packaging of each new HP toner cartridge contains information on how to participate in this programme. Or visit our website: http://www.hp.com/recycle.

Yields of consumables

The HP toner cartridges CLT-Y506S, CLT-M506S, CLT-C506S and CLT-K506S shipped with the product have a reference yield of 1,800/2,500 pages (colour/mono), determined according to ISO/IEC standard 19752.

The yield of these toner cartridges may be reduced as a consequence of the initial commissioning process or calibration processes of the printing system.

Information on handling of the toner modules

- Please leave HP LaserJet toner cartridge in its despatch packaging until you need it for use in your printer; when inserting the HP toner cartridge, please follow the information on handling.
- HP toner cartridges should never be opened by force. If toner dust escapes, e.g. as a result
 of inappropriate handling, inhalation of dust and skin contact are to be avoided as a
 precautionary measure.
- In case of skin contact wash affected areas thoroughly with soap and cold water. HP toner cartridges are to be kept out of the reach of children.

Air emissions

With original HP toners, the device passes the air emission test for monochrome and colour printing according to RAL-UZ 205. Since plastics of new electrical devices generally release small amounts of volatile substances into the room air, we recommend providing sufficient air exchange in rooms where new devices are set up.

Noise emissions

Declared sound power level for one-sided printing (L_{WAd}) In monochrome print mode 24 pages/minute: In colour print mode 24 pages/minute:

6.55 Bels and 65.5 dB 6.60 Bels and 66.0 dB

Energy

Energy information on Samsung CLX-6260FR

The consumption of electric power depends on its properties and on the way it is used. Samsung CLX-6260FR is designed and pre-set in a way to allow you to reduce electricity costs.

Directly after the last print or copy job, Samsung CLX-6260FR switches over to an electric power saving mode. If the device switches over to electric power saving modes, you can save electricity and operating costs. If the device is print or copy again, there can be a short delay – this is called return time. However, the device meets the strict Blue Angel requirements for a return time (http://www.blauer-engel.de).

You can save electricity costs by shortening the device's activation times as it will switch over to an electric power saving mode more quickly. If you extend the activation time or deactivate the electric power saving mode, you should consider that consequently the device will consume more electric power and might no longer meet the maximum value for electric power consumption of the Blue Angel. We recommend not extending the activation times.

The device is so designed as to ensure that it can be switched to the Off-mode (Hard switch) by pressing the on/off switch up to twice a day without suffering damage. This device does not have a switch by which it can be completely disconnected from the mains. When after having switched off the device you pull out the power plug, electric power consumption is completely stopped.

The table below lists the individual power consumption values as well as activation and return times (factory setting). With these values the device meets the Blue Angel requirements.

12 December 2017 / V1 2 of 3

Overview of Samsung CLX-6260FR operating modes

Page throughput for A4 paper size (according to ISO/IEC 24734):

In monochrome print mode: 24 pages/minute with a resolution of 239 dpcm (600 dpi) 1n colour print mode: 24 pages/minute with a resolution of 239 dpcm (600 dpi)

(dpcm = dots per centimetre [Bildpunkte pro Zentimeter]); (dpi = dots per inch [Bildpunkte pro Zoll])

Switch symbol	Operation mode ¹	Power consumption ² watts	Activation time ³ minutes	Return time seconds
Maximum power consumption (at switch-on): 1183 watts				
	Printing (continuous operation at 24 pages/minute), monochrome	442	immediately	immediately
	Ready	15	immediately	immediately
	Sleep mode	1.89	5 (1/5/10/15/30/60)	5
Ol	Off-mode (Hard switch)	0.1	switch activated	-
	Off-mode (Soft switch)	0.3	switch activated	_
	Disconnection from mains	0	e.g. pull out power plua	-

- After the last print or copy job, the device switches over to electric power saving modes in several steps. By and by, electric power consumption is reduced in these modes. The device will switch over to the Ready mode first. Then the device switches over to Sleep mode after the activation time stated above.
- Averaged value, measured without accessories.
- Activation time is the time that elapses after the end of the printing or copying process until the device enters the respective mode. The figures in brackets indicate the user-selectable range within which activation times can be adjusted. The activation time values apply to all primary functions of the device: printing, copying.

Energy consumption of Samsung CLX-6260FR

Measured according to the settings stated in the table above, the energy consumption of Samsung CLX-6260FR is 1.5 kilowatt-hours/week (energy consumption at standard use cycle according to ENERGY STAR version 2.0 (7-day week with 5 working days of 8 hours each) determined by using the test pattern A taken from ISO/IEC 10561:1999).

For the standard use cycle according to ENERGY STAR version 2.0 for this device, the following values were used: 24 print jobs per working day, each with 12 pages, single-sided at monochrome printing (288 pages/day).

Sign up for updates

hp.com/go/getupdated

