



## Technical data sheet

# Streichputz fein

### Product description

**Characteristics:**

- Non-slip and high quality brush-on plaster on dispersion basis
- Fine structure
- Structuring grout with good hiding and filling power
- Even structure when applied by roller
- Structuring possible when applied by brush
- Suitable as primer for following plasters
- Ideal underground for following varnishing
- For exterior and interior use
- Gloss level: mat
- With CE-labelling (Test certificate available on request)
- This product fulfills the requirements of the "Blue Angel" for low-emission interior wall paints RAL-UZ 102 (the Blue Angel is an environmental label organised by the federal government of Germany for the protection of people and the environment.)

### Material

<b>Application Area:</b>	For exterior and interior use on new and old solid undergrounds, such as stucco, concrete and gypsum board (without lignin marks). As priming coat for following applications with dispersion paints and resin plasters.
<b>Binding agent:</b>	Acrylic copolymer
<b>Colour:</b>	White
<b>Content of solids:</b>	Approx. 68 %
<b>Specific gravity:</b>	1.56 g/cm <sup>3</sup>
<b>pH value:</b>	Approx. 8.5
<b>Diluting agent:</b>	Water
<b>Viscosity:</b>	Slightly thixotropic

## Technical data sheet

# JONAS Streichputz fein

### Application characteristics

<b>Application:</b>	Brush / roller / spray (with special equipment).
<b>Underground:</b>	Needs to be clean, dry, and solid. Otherwise use JONAS Hydro-Haft-& Tiefgrund first to consolidate the underground. For underground treatment and application VOB, part C, DIN 18363 and the relevant BFS information must be observed.
<b>Coating build-up:</b>	Dilute priming coat with 5% water.
<b>Spreading rate per coating:</b>	Approx. 300 – 350 g/m <sup>2</sup> on smooth underground (if necessary test on the wall).
<b>Application temperature:</b>	At least + 5°C (Degrees Celsius) for air and underground during application and drying.
<b>Drying:</b>	The surface of the coating is touch-dry after 24 hours. Final hardness after approx. 2 weeks (at a temperature of 20 °C and a relative atmospheric humidity of 65 %).
<b>Remark:</b>	Application, drying and coating properties might be influenced by weather conditions (i.e. heat, wind, sun etc.).
<b>Tinting:</b>	Product can be tinted with JONAS Allcolor Vollton- und Abtönfarben. Tinting may lead to deviations in the technical data, also with respect to contents of preservatives.
<b>Cleaning of tools:</b>	Clean with water immediately after use.

### General information

<b>Storage:</b>	Cool, but not freezing.
<b>Shelf-life:</b>	Can be stored for at least 12 months after date of filling (see additional sticker) if stored properly in the unopened original packaging.
<b>Art.No. and description:</b>	31 00 001 JONAS Streichputz fein
<b>Packaging:</b>	20 kg / 8kg
<b>Ingredients acc. to. VdL RL01:</b>	Acrylic copolymer, white pigment, calcium carbonate, water, additives, preservative: BIT / MIT / Zinc pyrrithione.
<b>Safety:</b>	Please follow the instructions of the safety data sheet.
<b>Labelling:</b>	This product is not classified according to EU regulation No 1272/2008 [CLP].
<b>Product-code:</b>	BSW20
<b>VOC content:</b>	EU limit for the product Kat. A/a: 30 g/l (2010). This product contains < 1 g/l VOC.
<b>Waste disposal:</b>	Empty containers can be disposed for recycling. Any dried residues of material can be disposed of as construction waste or together with domestic garbage. Containers with liquid material residues must be disposed of according to local regulations. For further information, please contact your local waste authority.


## Technical data sheet

# JONAS Streichputz fein

### General information

#### CE-labelling:

According to EN 15824 for stucco with organic binder for interior use.  
Declaration of performance no. 01-4

 JONAS GmbH & Co.KG Dieselstraße 42-44 42489 Wülfrath 11	Brandverhalten:	Klasse B-s1, d0 (bei Verwendung auf mineralischen Untergründen)
	Wasseraufnahme:	keine Leistung festgestellt
	Wasserdampfdurchlässigkeit $\mu$ :	keine Leistung festgestellt
	Haftfestigkeit:	$\geq 0,3$ MPa
	Dauerhaftigkeit (Frostwiderstand):	keine Leistung festgestellt
	Wärmeleitfähigkeit $\lambda_{10}$ , dry, mat:	keine Leistung festgestellt
EN 15824 Putz mit organischen Bindemitteln zur Verwendung im Innenbereich		

#### \*Flammability class B-s1, d0 (for use on mineral substrates.)

(The classification only applies if in practical use the construction product is used on base boards made of gypsum or base boards classified A1 or A2-s1, d0 according to DIN EN 13501-1 and with a gross density of 525 kg / m<sup>3</sup>).

**Water absorption:** no performance determined.

**Water vapour permeability  $\mu$ :** no performance determined.

**\* Adhesive strength:**  $\geq 0,3$  MPa

**Durability (frost resistance):** no performance determined.

**Thermal conductivity  $\lambda_{10}$ , dry, mat:** no performance determined.

#### Advice for use and safety acc. to CLP:

Keep out of reach of children. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Wear appropriate respiratory protection (full mask / half mask equipped with filter type A2/P2). Avoid eating, drinking and smoking during use of the product. Ensure good ventilation during and after application. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not empty into drains or water courses. Contains: 1,2-Benzisothiazol-3(2H)-on / 2-Methyl-2H-isothiazol-3-on, Zinc pyrithione. Safety data sheet available on request. Advice for people suffering from isothiazolinone allergy under phone-no.: +49(0)2058/789-0.