



Parquet flooring
Planks Alpine flame

by **MEISTER**





Bäckeralm oak 8834
vital / brushed / naturally oiled





*Nature
comes
home*



Planks Alpine flame:

PARQUET FLOORING FOR ALL THE SENSES

In a world that is spinning ever faster, we tend to concentrate on the essentials. On things that are original. Natural. On real wood! We rely on sustainability, quality and durability – and on authentic nature. Our Planks Alpine flame are a natural product in the best sense of the word – parquet flooring made of 100% naturally grown wood. Because we believe: Some thing only real wood can do!

This naturally grown wood forms room-filling, 2.20 metre long parquet planks in three layers. High-quality oak wood combined with careful surface treatment with handcrafted features, perfect down to the last detail – that's HAIN by MEISTER! The finishing touch to every plank is its natural oil finish. The valuable natural oil dries oxidatively – without any fuss. It forms a protective and at the same time breathable surface and, due to its soft and matt touch, particularly highlights the natural wood feel of oak planks. The result is an incomparably authentic parquet flooring whose every pore brings the vastness of nature into your home. You can see it, feel it and even smell it, because Alpine flame is the parquet flooring for all the senses.





Bäckeralm oak 8834
vital / brushed / naturally oiled



PURE NATURE. PURE PARQUET.

The Alpine flame planks are the perfect flooring solution for anyone who wants a natural and cosy ambience in their home and at the same time values solid craftsmanship with a modern touch and unmistakable character. With a thickness of 14 mm, the Alpine flame planks provide a solid and resilient foundation for a lifetime. And it will last longer than a single generation, because the 3.6 mm thick top layer of real wood can be sanded down many times. An added bonus for sustainability!

The high-quality core made of European spruce serves as the stable centre of the Alpine flame planks and, together with the click system, ensures that they can be laid safely and easily and do not deform even under heavy loads. The Alpine flame planks are oiled and ready to use and do not need to be treated after laying. Of course, final cleaning should still be carried out after laying. For normal cleaning, we recommend damp wiping with special parquet soap. Particularly stressed areas can simply be partially oiled as required. This will wipe away traces of use or small scratches, leaving the floor as good as new. To maintain the value of your parquet flooring so that you can enjoy it for years to come, treat your plank flooring with our HAIN Parquet Care Balm about once a year.



PRODUCT STRUCTURE

The Alpine flame planks feature a high-quality triple-layer construction made of 100% sustainable wood. The middle layer of spruce wood, together with the veneered backing, ensures optimum strength and stability. The wear layer, made of a 3.6 mm thick wood layer, can be sanded down many times, making it unsurpassably sustainable! The flooring is equipped with the stable Maxiclic click system and can be laid easily and floating without bonding.



www.blauer-engel.de/uz176



Parquet flooring Planks Alpine flame

- 1-strip (plank)
- Naturally oiled surface
- Longitudinal V-bevel and head-end
- Micro-bevel
- Click system: Maxiclic
- 30-year warranty* in living areas
- Approx. 3.6 mm wood wear layer
- Thickness: 14 mm
- Effective measurement: 2200 x 195 mm

* Warranty according to the MeisterWerke warranty conditions at www.meister.com

GRADINGS

Vital:

Real woods with strong colours and structures provide the basis for this range. The natural and raw character of the floor is emphasised by larger knots and varying degrees of cracks. There is no sapwood in this grading. Cracked knots and cracks are professionally filled. Small cracks that cannot be filled and knots may occur. Occasional cracked knots may appear and are expertly filled.

Harmonious:

It's all about the natural mix: For the "harmonious" grading, we choose woods with a calm look as well as a balanced and natural variety of hues. They contain a few tightly intergrown knots and brownwood and do not have any sapwood. Occasional cracked knots may appear and are expertly filled.







Mitteralm oak 8840
vital / brushed / naturally oiled





Stubenalm oak 8832

harmonious / brushed / naturally oiled



Staffelalm oak 8831

harmonious / brushed / naturally oiled



Rossfeldalm oak 8836

vital / brushed / naturally oiled



Kesselalm oak 8841

vital / brushed / naturally oiled





Kesselalm oak 8841
vital / brushed / naturally oiled





Bäckeralm oak 8834
vital / brushed / naturally oiled






Schärtenalm oak 8830
harmonious / brushed / naturally oiled




Bäckeralm oak 8834
vital / brushed / naturally oiled



Königstalalm oak 8837
vital / brushed / naturally oiled



Wettersteinalm oak 8833
harmonious / brushed / naturally oiled





Mitteralm oak 8840
vital / brushed / naturally oiled



Enzianalm oak 8839
vital / brushed / naturally oiled



Branderalm oak 8835
vital / brushed / naturally oiled



Herrenalm oak 8838
vital / brushed / naturally oiled





Mitteralm oak 8840
vital / brushed / naturally oiled







Kesselalm oak 8841
vital / brushed / naturally oiled






Mitteralm oak 8840
vital / brushed / naturally oiled




Accessories




BEAUTIFULLY VERSATILE: SKIRTING PROFILES AT A GLANCE




Skirting board
2 PK profile



Skirting board
3 PK profile




Skirting board
5 PK profile




Skirting board
6 profile




Skirting board
7 profile




Skirting board
8 PK profile




Skirting board
9 PK profile




Skirting board
10 PK profile
10 F MK profile




Skirting board
11 PK profile
11 F MK profile




Skirting board
12 PK profile
12 F MK profile




Skirting board
13 PK profile




Skirting board
14 MK profile
14 F MK profile




Skirting board
15 PK profile
15 F MK profile




Skirting board
16 MK profile




Skirting board
17 PK profile




Skirting board
18 PK profile




Skirting board
19 PK profile




Skirting board
20 PK profile




Skirting board
20 PK Aqua profile



Skirting board
21 F MK profile



Skirting board
22 F MK profile



Skirting board
23 F MK profile

PK | MK profile:
MDF base material
(PK Aqua:
ABS base material)

F MK profile:
Spruce base material



‘HOW TO’: MOULDINGS ACCESSORIES

To ensure that even difficult corners and edges fit perfectly, MEISTER offers internal corners, external corners, end caps and connection pieces to match many mouldings. Visit www.meister.com to see the complete range. Here, you will also find an overview of the different profiles available for aligning adjacent floorings or French windows, suitable radiator rosettes, door stoppers and our recommended cleaning and protective care agents.



Kesselalm oak 8841
vital / brushed / naturally oiled



THE COMPLETE SYSTEM COUNTS: UNDERLAYS FOR HIGH-QUALITY FLOORING

Without a good underlay, it's not a good floor: The underlay material has a significant influence on the durability of the flooring and is an important component of how the entire system functions as far as day-to-day wear is concerned. Premium-quality flooring may suffer damage when laid on poor-quality underlay.

High-quality underlay, on the other hand, ensures that your flooring will bring you lasting enjoyment; it prevents damage to the click connections through optimum pressure stability, for example, whereas excessively soft underlay can have a significantly negative effect on fold-down connections. When choosing an underlay material, both the sub-flooring and the flooring to be installed are important. Whether your sub-flooring is concrete, wooden floorboards, drywall or existing flooring such as tiles or stone:

With a comprehensive underlay range, MEISTER ensures that every MEISTER floor can be laid on your sub-flooring.

Sub-flooring / Underlay	Silence 25 DB	Silence 20	Silence 15 DB	PE film
Wooden planks	–	✓	–	–
Wood based boards, OSB boards, drywall elements	–	✓	–	–
Mineral subfloors (e.g. cement screed, anhydride screed)	✓	✓ with PE film	✓	✓
Mastic asphalt screed	–	✓	–	–
Existing coverings (e.g. ceramic tiles and boards, natural stone, plastic)	✓	✓ with PE film	✓	✓



THE MEISTER UNDERLAY MATERIALS:

The special PUR mineral blend makes MEISTER-Silence 25 DB, MEISTER-Silence 20 or MEISTER-Silence 15 DB the ideal insulating underlay for effective room and footfall noise protection. The high self-weight of the products also has a positive effect on the sound-absorbing properties. In the case of Silence 25 DB and 15 DB the moisture barrier is already integrated, eliminating the need to lay an additional PE film.

All MEISTER underlay materials can be installed on underfloor heating. They comply with the technical bulletin provided by the European Producers of Laminate Flooring (EPLF) based on CEN/TS 16354. The Silence products also meet the requirements of the technical bulletin issued by the Multilayer Modular Flooring Association (MMFA): “Underlay Materials under Multilayer Modular Floor Coverings (MMF) – Test Standards and Performance Indicators” for Class 1 (with HDF core).



MEISTER Silence 25 DB with
integrated vapour barrier | 3 mm

MEISTER Silence 20 | 2.5 mm

MEISTER Silence 15 DB with
integrated vapour barrier | 2 mm









© 2020 by MeisterWerke Schulte GmbH
Colours and textures may vary due to printing conditions.
We reserve the right to make changes. No responsibility is assumed for errors.

MEISTER – a MeisterWerke Schulte GmbH brand
Johannes-Schulte-Allee 5 | 59602 Rùthen-Meiste | GERMANY
Phone +49 2952 816-0 | Fax +49 2952 816-66 | www.meister.com

GB