

# Südwest Grundierfarbe Spezial

### Product description

- Characteristics:**
- White pigmented priming paint
  - For interior use
  - Ideal compensation of colour variations of the underground
  - Very good hiding power
  - Perfectly balances absorbency of the substrate
  - Excellent grip of following wallpapers
  - This product fulfills the requirements of the "Blue Angel" for low-emission interior wall paints RAL-UZ 102 (the Blue Angel is an environmental label organised by the federal government of Germany for the protection of people and the environment.)
- \* Certificate available on request.
- DIN EN 13300:**
- Wet scrub resistance: class 2
  - Contrast ratio: hiding power class 1 ( $\geq 99.5$ ) at a spreading rate of 165 ml/m<sup>2</sup>
  - Gloss level: dull mat
  - Maximum particle (grit) size: fine ( $< 100 \mu\text{m}$ )

### Material

- Application Area:** For interior use on good, solid new and old undergrounds such as stucco, concrete, woodchip paper, gypsum board (without lignin marks).
- Binding Agent:** Vinyl acetate dispersion
- Colour:** White
- Content of Solids:** Approx. 64 %
- Specific gravity:** 1.57 g/cm<sup>3</sup>
- pH value:** Approx. 9
- Diluting agent:** Water
- Viscosity:** Slightly thixotropic



## Technical data sheet

# Südwest Grundierfarbe Spezial

### Application Characteristics

<b>Application:</b>	Brush / roller / spray (airless).
<b>Underground:</b>	Needs to be clean, dry, and solid. Otherwise use suitable primer first to consolidate the underground. For underground treatment and application VOB, part C, DIN 18363 and the relevant BFS information must be observed.
<b>Coating build-up:</b>	Without dilution.
<b>Spreading rate per coating:</b>	Approx. 150 ml/m <sup>2</sup> on smooth underground (if necessary test on the wall).
<b>Application temperature:</b>	At least + 5°C (Degrees Celsius) for air and underground during application and drying.
<b>Drying:</b>	The surface of the coating is dry and can be painted over after 8 - 10 hours (at a temperature of 20 °C and a relative atmospheric humidity of 65 %).
<b>Cleaning of tools:</b>	Clean with water immediately after use.

### General information

<b>Storage:</b>	Cool, but not freezing.
<b>Shelf-life:</b>	Can be stored for at least 12 months after date of filling (see additional sticker) if stored properly in the unopened original packaging.
<b>Packaging:</b>	4.8 l / 1000 l
<b>Ingredients acc. to VdL RL01:</b>	Vinyl acetate dispersion, white pigment, calcium carbonate, silicate, water, additives, preservative, BIT / MIT / Zinc pyrithione.
<b>Safety:</b>	Please follow the instructions of the safety data sheet.
<b>Labelling:</b>	This product is not classified according to EU regulation No 1272/2008 [CLP].
<b>Product-code:</b>	BSW20
<b>VOC content:</b>	EU-Limit for the product Kat. A/a: 30 g/l (2010). This product contains < 1 g/l VOC.
<b>Waste disposal:</b>	Empty containers can be disposed for recycling. Any dried residues of material can be disposed of as construction waste or together with domestic garbage. Containers with liquid material residues must be disposed of according to local regulations. For further information, please contact your local waste authority.
<b>Advice acc. to CLP:</b>	Keep out of reach of children. Wear appropriate respiratory protection (full mask / half mask equipped with filter type A2/P2). Avoid eating, drinking and smoking during use of the product. Ensure good ventilation during and after application. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not empty into drains or water courses. . Contains: 1,2-Benzisothiazol-3(2H)-on / 2-Methyl-2H-isothiazol-3-on / Zinc pyrithione. May produce an allergic reaction. Advice for people suffering from isothiazolinone allergy under phone-no.: +49(0) 6324/709-0.