

Specifications Sheet

FIBREBOARD HARD

Fibre board is a rigid, high density paperboard and has applications in the automotive industry, infiles, boxes, welding shields and much more.

Colours:	black		
Thickness:	1,0 – 2,80 mm		
Basis weight:	1000 - 2800 g/m ²		
Tolerance:	basis weight and thickness +/- 5 %		
Machine size:	< 1200 g/m ² : 242 x 308 cm > 1200 g/m ² : 244 x 308 cm		
Standard sizes:	122 x 154 cm LG*	81 x 154 cm LG	61 x 154 cm LG
	122 x 102 cm SG*	81 x 102 cm LG	61 x 102 cm LG
	122 x 77 cm SG	81 x 77 cm SG	61 x 77 cm LG
	122 x 61 cm SG	81 x 61 cm SG	61 x 61 cm

*LG = long grain; The fibres run parallel to the longer side.

*SG = short grain; The fibres run parallel to the shorter side.

Special sizes:	on request
Processing:	<p>machine sizes</p> <p>Angle cuts – possible with guillotine cutter and circular shears</p> <p>punching – maximum punching size 118x82 cm or 122x88 cm (depends on size and quantity)</p> <p>rounded and canted counters</p> <p>staked off and bundled</p> <p>creasing, scratching</p> <p>varnishing</p> <p>covering: corrosion resistant and electro conductive</p> <p>embossing: leather, hippo, Macro or Opaco embossing</p>
Minimum quantity:	black – 1000 kg per size and thickness



Das Zeichen für
verantwortungsvolle
Waldwirtschaft