

# Blue Angel Environmental Information and Data Sheet Model: IM 350F

EDP: 418486

Issued: July 15th 2021

1 General Specification						
Primary functions of the base unit						
Model : IM 350F		□ Copy	□ Print	☐ Fax	⊠ Scan	
Tachnology						
Technology		☑ Electrophotographic		☐ Inkjet Techn	☐ Inkjet Technology	
Print Speed Simplex, DIN-A4 pagaccording to ISO/IEC 24734	ges/min,	Monochrome: 3	5	Colour: NA		
Copying Speed Simplex, DIN-A4 according to ISO/IEC 24735	pages/min,	Monochrome: 3	35	Colour: NA		
The system is designed for use it	in the professio	nal/commercial	sector.			
2 Technical Safety (Declaration	on of Conformit	у				
The system complies with the fo	llowina EU reau	ılations as far a	s they are app	licable and bears t	the CE mark	
The system complies than all le			oy a.o app			
<ul><li>Radio Equipment Directive 201</li><li>RoHS Directive 2011/65/EU</li></ul>	4/53/EU					
ErP Directive 2009/125/EC						
3 Environmental Labels						
www.blauer-engel.de/uz219						
The requirements of the Blue Angel DE-UZ 219 eco-label were tested and met with the toner supplied and recommended by Ricoh. Further information on the Blue Angel can be found at: <a href="https://www.blauer-engel.de/en">https://www.blauer-engel.de/en</a>						
4 Use and labelling of materials						
Paper	The device is suitable for processing recycled paper that complies with EN 12281:2002. We recommend using the machine in duplex mode (double-sided copy/print). The model is equipped with a duplex and N-up function:  ☐ Optional					
Toner/ Ink	☑ Toner ☐ Ink					
Ames-Test	Negative (refer to Safety Data Sheet)					
Photo Conductor Unit	Organic Photo Conductor (OPC)					
Batteries	Mangandioxide Lithium free of lead, cadmium and mercury					
No halogenated flame retardants are used in housing parts and other plastic parts are used in housing parts			ier plastic parts over			

System: IM 350F Ausgabe: July 15th 2021

Seite 2 von 4



Marking of Plastic Parts	All plastic parts >25g are marked in accordance with ISO 11469:2000 and ISO 1043.				
Proportion by weight of recycled plastic relative to total plastic (Post-consumer)	□ 0 – 1 % □ 1 – 5 % □ 5 – 10 %		☐ 10 – 15 % ☐ 15 – 20 % ☐ 20 – 25 %		
Legal requirements for recycling (WEEE)	The device fully complies with WEEE requirements.				
5 Yield of consumables					
Consumable	Description	EDP	Yield (A4)	Test Procedure	
Toner Cartridges	Print Cartridge IM 350	418133	9,000	A4, 6% Coverage	

**Note on the ranges given here:** The actual yield depends on the image size and brightness, the number of pages to be printed at one time, the type and size of paper used, the contents of the printed images, and environmental conditions such as temperature and humidity. Refer to the system's Operation Guide for more information on run times and the change intervals of consumables.

**Note on handling the toner containers:** Do not open the toner containers. When replacing them, please follow the instructions in the operating manual. Do not inhale any leaking toner as a result of improper handling, but wipe it off with a damp cloth. Avoid skin contact. If toner gets onto the skin, wash affected areas with plenty of cold water and soap. **Keep toner (old or new) out of the reach of children!** 

## 6 Warranty and spare parts

The guarantee for the devices corresponds to the legal regulations, as far as these are binding. All Ricoh distributors and subsidiaries offer all-in service contracts that go beyond the legal warranty. Please contact your local Ricoh office or distributor. Consumables and essential spare parts are available at least 5 years after the last unit in this series was sold.

# 7 Cleaning and Maintenance

Cleaning, maintenance and disposal activities may only be carried out by qualified personnel. Further information on cleaning and maintenance of the system can be found in the chapter "Maintenance and Specification" of the operating instructions.

8 Power Consumption	Determined according to DE UZ 219 and ENERGY STAR® in delivery condition			
Operating Mode	erating Mode Default Delay Time Return Time <sup>2)</sup> (s)			
Maximum Power Consumption			1098	
Continuous Operation 35 ppm (15 min. printing time) monochrom			562	
Ready	0 0		92.4	
Sleep Mode	1 or press energy saving button	17	0.8	
Off Mode	Switch	Switch		
TEC (Typical Electricity Consumption) based on ENERGY STAR® 3.0 test method			0.45 kWh/week	

<sup>1)</sup> Default Delay Time: The time that elapses after the end of the printing process until the device automatically switches to an idle state.
2) Return Time: The time it takes for the device to return from an energy-saving state to a print-ready state.

System: IM 350F Ausgabe: July 15th 2021

Seite 3 von 4



This product is designed to save energy costs. The system automatically reduces energy consumption when not used for a period of time (1 minute). This mode is called Sleep Mode. From these states, the machine returns to standby printing in a short time (the return time listed above) when it receives a print or copy job. This allows you to save energy without limiting your productivity. With its return time, the system meets the high requirements of the Blue Angel, which attaches particular importance to user-friendliness in this respect.

The activation times for the sleep mode can be changed by the user in the range 1-60 minutes.

However, if the activation times are increased, this leads to higher energy consumption and thus to higher electricity costs. It is therefore recommended not to change the preset activation times.

When the main switch is actuated, there is still a low power consumption of max. 0.2 watts. Complete disconnection from the mains can be achieved by pulling the mains plug. Please observe the instructions in the operating instructions in order to prevent damage to the system and possible loss of data.

The device is designed so that it can be switched off at least twice a day.

**Note on TEC (Typical Electricity Consumption).** The aim of the TEC method is to determine the energy efficiency of hardcopy devices (copiers, printers, multifunction systems) and to make them comparable. The method determines the energy consumption of a product over a fixed period of time under normal operating conditions.

## The following usage cycle is assumed for the present system:

Per working day 32 print jobs with 19 pages, simplex at monochrome printing, (608 pages/day).

Hence, the energy consumption for a week in standard usage cycle according to ENER-GY STAR® (7-day-week with 5 working days of 8 hours) is 0.45 kWh per week.

#### 9 Noise Emissions

#### 9.1 According to DE-UZ 219 clause 3.5 printing mode

Declared Sound Power Level (Lwac in dB(A) )BW	62.7
---	------

## 9.2 According to ISO 7779 in combination with ISO 9296

	Standby	Operation Monochr.	Operation Col.
Sound Power Level (LwA dB(A))	30.6	60.1	NA
Declared Sound Power Level (Lwad B(A))	3.4	6.3	NA
Sound pressure level (L <sub>pA</sub> dB(A) )operator position	22.5	53.4	NA
Sound pressure level (L <sub>pA</sub> dB(A) ) bystander position	23.9	52.0	NA

## 10 Chemical emissions determined according to ISO/IEC 28360 with DE-UZ 219

		Monochrome		Full Colour	
		Measured Value	Reference value DE-UZ 219 (Blue Angel Mark)	Measured Value	Reference value DE-UZ 219 (Blue Angel Mark)
Pre-Operating Phase	TVOC [mg/h]	0.036	2	NA	2
	TVOC [mg/h]	2.0	10	NA	18
	Benzene [mg/h]	< LOD	< 0,05	NA	< 0,05
Printing Phase (Sum of	Styrene [mg/h]	0.056	1,0	NA	1,8
Printing and Pre-operating phase)	Non identified VOC [mg/h]	0.088	0,9	NA	0,9
priase)	Ozone [mg/h]	< LOD	1,5	NA	3,0
	Dust [mg/h]	< LOD	4,0	NA	4,0
Printing Phase	PER10 PW [Partikel/10min]	1.9 * 10 <sup>11</sup>	3,5 * 10 <sup>11</sup>	NA * 10 <sup>11</sup>	3,5 * 10 <sup>11</sup>

System: IM 350F Ausgabe: July 15th 2021 Seite 4 von 4



sufficient air exchange in the in few days after the unit has bee The system is equipped with ar The system is equipped with du	lew electronic devices generally emit volatile substances into the room air. For this reason, stallation rooms and, if necessary, at the workplace should be ensured, especially in the first n installed.  n ozone filter:  Yes:  Not applicable:			
11 Recycling				
Empty toner cartridges	☐ Collection via Ricoh Resource Smart Return Program			
Full toner cartridges	Filled waste toner containers should not be disposed of with household and commercial waste. They can be handed in at any RICOH branch and at any RICOH contractual partner.			
Waste Toner	<ul> <li>□ Not applicable.</li> <li>☑ Please dispose according to local legislation</li> </ul>			
Batteries	<ul><li>☐ Collection according to local legislation.</li><li>☐ No battery used.</li></ul>			
Photo Conductor units and spare parts	⊠ Return via Ricoh Resource Smart Return Program			
Devices	Used equipment is taken back and recycled in an environmentally friendly manner or - if this is no longer possible - recycled.  Information about collection points for used RICOH products in your country can be obtained from your dealers or via the RICOH website:  Contact: <a href="https://www.ricoh-europe.com">https://www.ricoh-europe.com</a>			
Information on Ricoh's pan-European consumables collection system can be found on the following website: <a href="https://www.ricoh-return.com">https://www.ricoh-return.com</a>				
12 Other				
All information in this data sheet is based on the current state of our knowledge. They do not represent any assurance of the properties of the product described within the meaning of the statutory warranty regulations.				

Latest Change:

new