




LayRed Skirting

Technical data sheet
English

General information

Standard skirtings that match the colour of your floor.



Contents

6 x skirting

Composition

Polystyrene

Colour

Colour matched

Packaging

Headcartons and shrink-wrapping

-

Order code

MODVSKL

Dimensions

2400 x 12 x 58 mm

Applicable for:

Moduleo LayRed floors.

The floor must be able to expand and contract on all sides. This is why an expansion gap must be provided on all sides of the floor, around pipes, thresholds and under door frames. The exact expansion joint size depends on the floor type. Consult the installation instructions of your Moduleo floor to know the required size of the expansion gap. To finish off this gap, we offer a wide range of skirting and profiles.

Features

Moduleo accessories are specifically developed for Moduleo floors.

Perfectly matching colour

The identical connection with your Moduleo LayRed floor.

Waterproof

Just as water resistant as your floor.

Scratch and wear resistant top layer

The durable top layer helps to protect the skirtings, scotias and profiles against everyday wear and tear.

Installation

The skirting can be installed in the following way:

- 01 It is recommended to use a new saw blade when cutting the skirting. Position the skirting with the decorative side facing up and align the top of the profile towards you for optimal results.
- 02 Attach the skirting to the wall with the Moduleo Omni glue.

Unilin bv division flooring
Ooigemstraat 3, B-8710 Wielsbeke
T: +32 56 67 52 11
unilin.com
quick-step.com

