



Technical Data Sheet

Quality Specification

Palm Print 68

	Basis Weight	Bulk	Brightness	Breaking Length (MD)	Opacity	Roughness (TS/BS) Bendtsen
Dimension	[g/m ²]	[cm ³ /g]	[%]	[m]	[%]	[ml/min]
Standard	ISO 536	ISO 534	ISO 2470	ISO 1924	ISO 2471	ISO 8791-2
	45.0	1.2 - 1.4	68	5,500	93.0	120 - 180
	48.8	1.2 - 1.4	68	5,500	94.0	120 - 180
	52.0	1.2 - 1.4	68	5,500	95.0	120 - 180

Colour Specification:	Standard ISO 5631	L* (C/2°) 87.0 a* (C/2°) -0.5 - 0.0 b* (C/2°) 2.0 - 3.0
Preconditioning:	ISO 187, 23°C, 50% relative humidity	
Tolerance:	The tolerances are within the industrial standard range.	
Certificates:	ISO 9001, ISO 14001, ISO 45001, ISO 50001, FSC®, PEFC, Blue Angel, EU Ecolabel (Note our licence numbers: FSC® C127275, FSC® C041166, PEFC/04-31-2442.)	
PrePress Guidelines:	ICC Paper Profile: PSO_INP_Paper_eci.icc Characterisation data: FOGRA48L.txt	

Issue date 1 January 2021



Technical Data Sheet

Quality Specification

Palm Print 68 H

	Basis Weight	Bulk	Brightness	Breaking Length (MD)	Opacity	Roughness (TS/BS) Bendtsen
Dimension	[g/m ²]	[cm ³ /g]	[%]	[m]	[%]	[ml/min]
Standard	ISO 536	ISO 534	ISO 2470	ISO 1924	ISO 2471	ISO 8791-2
	45.0	1.1 - 1.3	68	5,500	93.0	40 - 80
	48.8	1.1 - 1.3	68	5,500	94.0	40 - 80
	52.0	1.1 - 1.3	68	5,500	95.0	40 - 80

Colour Specification:	Standard ISO 5631	L* (C/2°) 87.0 a* (C/2°) -0.5 - 0.0 b* (C/2°) 2.0 - 3.0
Preconditioning:	ISO 187, 23°C, 50% relative humidity	
Tolerance:	The tolerances are within the industrial standard range.	
Certificates:	ISO 9001, ISO 14001, ISO 45001, ISO 50001, FSC®, PEFC, Blue Angel, EU Ecolabel (Note our licence numbers: FSC® C127275, FSC® C041166, PEFC/04-31-2442.)	
PrePress Guidelines:	ICC Paper Profile: PSO_INP_Paper_eci.icc Characterisation data: FOGRA48L.txt	

Issue date 1 January 2021

www.palm.de