

wineo

THAT'S FLOORING



wineo 1000

PURLINE ORGANIC FLOORING

**NATURAL INGREDIENTS
FOR A HEALTHY LIFESTYLE**

CONTENT

The ecuran organic formula	02
Product advantages	05
Product composition	06
wineo 1000 wood	08
wineo 1000 wood XXL Multi-Layer	18
wineo 1000 stone	24
PERFECT FIT Accessories	28
Quality and awards	30
Technical characteristics	32

BEST INGREDIENTS FOR BEST RESULTS

wineo PURLINE organic flooring is a high-quality polyurethane flooring solution made from the finest materials. The basis is provided by ecuran, a high-performance composite material that is manufactured primarily from plant-based oils such as canola oil or castor oil and naturally-occurring mineral components such as chalk. wineo PURLINE organic flooring impresses most of all with its sustainability, combined with its extreme hard-wearing features; furthermore, it is truly made in Germany throughout all of its production stages.



CANOLA OR CASTOR OIL

Natural and sustainable – the perfect replacement for plasticisers and crude oil

CHALK

Harmless and particularly fine – an ideal filler



Made with

ecuran

your flooring upgrade

The unique bio-polyurethane from the Windmüller house now has a name: ecuran

ecuran is the sustainable high-performance composite material for sophisticated flooring solutions. It is based on "bio-polyurethane" which is manufactured to a large extent from plant-based oils such as canola oil or castor oil and naturally occurring mineral components such as chalk. Detailed information regarding ecuran can be found here: www.ecuran.de

BEST INGREDIENTS FOR FRESH INTERIOR DESIGN IDEAS

Flooring made from natural raw materials – that convinces a lot of people.
But flooring that withstands an unbelievable amount of pressure – that impresses everyone.
Acquire a taste for it!



DURABLE

wineo organic flooring is **resistant to staining**. Even furniture and chair castors **leave no trace**.



UV-RESISTANT

Even when exposed to sunlight:
The organic flooring **doesn't fade** with exposure to sunlight.



EASY CARE

The polyurethane surface makes the organic flooring **easy to clean**.



SUITABLE FOR DAMP AREAS

In the **kitchen or bathroom**: PURLINE organic flooring shows its best side in every situation.



QUIET

The soft surface ensures pleasantly **quiet acoustics**.



GENTLE ON THE ANKLES

Health-conscious: The elastic surface is gentle on the joints.



WARM TO THE FEET

The organic flooring feels **pleasantly warm** and is perfect for lounging, playing and living.



NON-SLIP

The tested surface ensures **safety with every step**.



SUITABLE FOR UNDERFLOOR HEATING

More comfort: Installed over underfloor heating, the organic flooring provides additional **cozy warmth**.



ODOUR NEUTRAL

Please do not disturb: **no unpleasant odours** or dangerous evapourations.

NATURAL TALENT FOR YOUR HOME

In addition to sustainability and longevity, wineo 1000 scores with three product qualities. Depending on the area of application and the subsurface qualities, you will always find the right product with wineo 1000. A sustainable, all-round talent with design aspirations.

wineo 1000 wood | stone



- 1 Top element**
PU-top layer with surface structure, decor paper & stabilisation
- 2 Base layer**
ecuran high-performance composite material
- 3 Backing**
Integrated FleeceTEC-System® for easy and comfortable installation

i



Application area
perfectly suited for new constructions and prepared substrates.

Special product features

- low structural height of 2.2 mm
- elastic flooring

Installation type: gluing

- gluing onto the existing subsurface or the underlay silentPLUS
- room walking sound is reduced

Installation type: floating

- installation onto the self-adhesive silentPREMIUM underlay
- quick, easy and tidy

Subsurface
the surface must be permanently dry, load-bearing, tidy and even.
(levelled out for gluing process)

Accessories/Installation support

- matching skirting boards for all wood decors (pg. 29)
- underlays silentPREMIUM and silentPLUS (pg. 28)
- the cutter knife, for a simple and tidy cut

wineo 1000 wood | stone



- 1 Top element**
PU-top layer with surface structure, decor paper & stabilisation
- 2 Profile connection**
Connect-technology
- 3 Base layer**
ecuran high-performance composite material
- 4 Backing**
Integrated FleeceTEC-System® for easy and comfortable installation

i



Application area
perfectly suited for new constructions and prepared substrates

Special product features

- low structural height of 5 mm
- elastic flooring

Installation type: floating

- installation for clicking in
- quick, easy and tidy

Subsurface
the surface must be permanently dry, load-bearing, tidy and even.

Accessories/Installation support

- matching skirting boards for all wood decors (pg. 29)
- underlay mat silentCOMFORT (pg. 28)
- the cutter knife, for a simple and tidy cut

wineo 1000 wood XXL Multi-Layer



- 1 Top element**
PU-top layer with surface structure, decor paper & stabilisation with ecuran
- 2 Profile connection**
Fold-Down locking
- 3 Core board**
Swell-protected Aqua-Protect® HDF core board
- 4 Underlay**
Integrated underlay SoundPROTECT for an impact sound reduction of up to 15 dB

i



Application area
perfectly suited for new constructions or installation on existing floor coverings according to DIN 18202.

Special product features

- helps to minimise subfloor imperfections and minor bumps
- integrated underlay reduces walking and impact noise levels by up to 15 dB

Installation type: floating

- installation for clicking in

Subsurface
the surface must be permanently dry, load-bearing, tidy and even.

Accessories/Installation support

- matching skirting boards for all wood decors (pg. 29)
- PE vapor barrier for installation on mineral substrates
- saw or laminate cutter

wineo 1000 wood

Installation type: Glue



1298 × 200 mm

Product thickness: 2.2 mm

Planks / Box: 20/5.19m²

Installation type: Click



1295 × 195 mm

Product thickness: 5 mm

Planks / Box: 8/2.02m²



Nordic Pine Style
Glue: PL049R
Click: PLC049R




Malmoe Pine
Glue: PL019R
Click: PLC019R



Arctic Oak
Glue: PL008R
Click: PLC008R



Ascona Pine Nature
Glue: PL052R
Click: PLC052R



BEST INGREDIENTS FOR CAREFREE USE

wineo 1000 wood

Installation type: Glue
Product thickness: 2.2 mm
Planks / Box: 20/5.19m²



1298 x 200 mm

Installation type: Click
Product thickness: 5 mm
Planks / Box: 8/2.02m²



1295 x 195 mm



Island Oak Moon
 Glue: PL045R
 Click: PLC045R




Calistoga Grey
 Glue: PL003R
 Click: PLC003R



Valley Oak Mud
 Glue: PL042R
 Click: PLC042R



Patina Teak
 Glue: PL046R
 Click: PLC046R



BEST INGREDIENTS IN THEIR MOST BEAUTIFUL FORM

Calistoga Grey
 wineo 1000 wood | PL003R
 wineo 1000 wood | PLC003R
 wineo 1000 wood XXL | MLP003R

wineo 1000 wood

Installation type: Glue
Product thickness: 2.2 mm
Planks / Box: 20/5.19m²



1298 x 200 mm

Installation type: Click
Product thickness: 5 mm
Planks / Box: 8/2.02m²



1295 x 195 mm



Nordic Pine Modern
Glue: PL050R
Click: PLC050R




Traditional Oak Brown
Glue: PL051R
Click: PLC051R



Calistoga Cream
Glue: PL054R
Click: PLC054R



Island Oak Sand
Glue: PL044R
Click: PLC044R



**BEST INGREDIENTS FOR
HEALTHY WORKING**

Calistoga Cream
 wineo 1000 wood | PL054R
 wineo 1000 wood | PLC054R
 wineo 1000 wood XXL | MLP054R

wineo 1000 wood

Installation type: Glue
Product thickness: 2.2 mm
Planks / Box: 20/5.19m²



Installation type: Click
Product thickness: 5 mm
Planks / Box: 8/2.02m²



Valley Oak Soil
 Glue: PL041R
 Click: PLC041R



Dakota Oak
 Glue: PL017R
 Click: PLC017R



Garden Oak
 Glue: PL005R
 Click: PLC005R



Island Oak Honey
 Glue: PL043R
 Click: PLC043R



BEST INGREDIENTS FOR TASTEFUL LIVING

Dakota Oak
 wineo 1000 wood | PL017R
 wineo 1000 wood | PLC017R
 wineo 1000 wood XXL I MLP017R

wineo 1000 wood

Installation type: Glue



1298 x 200 mm

Product thickness: 2.2 mm

Planks / Box: 20/5.19m²

Installation type: Click



1295 x 195 mm

Product thickness: 5 mm

Planks / Box: 8/2.02m²



Carmel Pine
Glue: PL048R
Click: PLC048R



Summer Beech
Glue: PL047R
Click: PLC047R



Canyon Oak
Glue: PL007R
Click: PLC007R



Calistoga Nature
Glue: PL001R
Click: PLC001R



BEST INGREDIENTS FOR THE PERFECT FLOORING EXPERIENCE

Carmel Pine
wineo 1000 wood | PL048R
wineo 1000 wood | PLC048R

wineo 1000 wood XXL Multi-Layer

Installation type: Click
Product thickness: 9mm
Planks / Box: 5/2.19m²



Multi-Layer

1845 x 237 mm



Installed area Canyon Oak | all-round V4 joint



Canyon Oak | Click: MLP007R | all-round V4 joint



Installed area Island Oak Sand | all-round V4 joint



Island Oak Sand | Click: MLP044R | all-round V4 joint



Installed area Calistoga Nature | all-round V4 joint



Calistoga Nature | Click: MLP001R | all-round V4 joint



Installed area Calistoga Cream | all-round V4 joint



Calistoga Cream | Click: MLP054R | all-round V4 joint

wineo 1000 wood XXL Multi-Layer

Installation type: Click
Product thickness: 9mm
Planks / Box: 5/2.19m²



Multi-Layer

1845 x 237 mm



V4

Installed area Island Oak Moon | all-round V4 joint



Island Oak Moon | Click: MLP045R | all-round V4 joint



V4

Installed area Valley Oak Soil | all-round V4 joint



Valley Oak Soil | Click: MLP041R | all-round V4 joint



V4

Installed area Calistoga Grey | all-round V4 joint



Calistoga Grey | Click: MLP003R | all-round V4 joint



V4

Installed area Dakota Oak | all-round V4 joint



Dakota Oak | Click: MLP017R | all-round V4 joint

wineo 1000 stone

Installation type: Glue
Product thickness: 2.2 mm
Tile / Box: 14/4.86m²



862 x 402 mm

Installation type: Click
Product thickness: 5 mm
Tile / Box: 6/2.05m²



859 x 397 mm



Stockholm Loft
Glue: PL055R
Click: PLC055R



Mocca Cream
Glue: PL039R
Click: PLC039R



Venice Harbour
Glue: PL056R
Click: PLC056R



Milan Opera
Glue: PL059R
Click: PLC059R



**BEST INGREDIENTS FOR
 NATURAL RESISTANCE**

wineo 1000 stone

Installation type: Glue

Product thickness: 2.2 mm

Tile / Box: 14/4.86m²



Installation type: Click

Product thickness: 5 mm

Tile / Box: 6/2.05m²



Paris Art
Glue: PL057R
Click: PLC057R




Puro Silver
Glue: PL028R
Click: PLC028R



Manhattan Factory
Glue: PL058R
Click: PLC058R



Scivaro Slate
Glue: PL038R
Click: PLC038R



BEST INGREDIENTS FOR IMPRESSIVE PERFORMANCES

Paris Art
 wineo 1000 stone | PL057R
 wineo 1000 stone | PLC057R

PERFECT FIT ACCESSORIES

UNDERLAY MATERIAL

We recommend using our silentPREMIUM, silentPLUS or silentCOMFORT underlay material with wineo 1000. It is made by ecuran. The basis is provided by ecuran, a high-performance composite material that is manufactured primarily from plant-based oils such as canola oil or castor oil and naturally-occurring mineral components such as chalk.



Detailed information can be found in our accessory brochure Art.-no. 20091021.

- fast, energy-efficient distribution of ground heat
- excellent noise reduction with hard and soft floor coverings
- long-life performance of at least 30 years
- recovery almost 100%
- sustainable raw materials
- without chlorine, plasticisers or solvents



silentPREMIUM

The premium class for the floating installation of elastic floor coverings for gluing.



Self-adhesive top surface, floating installation, ultra-fast.
Impact sound reduction:
Up to 15 dB in the system with wineo 1000 for gluing.
Art.-no. UPU1010

silentPLUS

Extra quietness for full-surface bonding of elastic floor coverings for gluing.



Full-surface bonding above, self-adhesive below, ultra-quiet.
Impact sound reduction:
Up to 17 dB in the system with wineo 1000 for gluing.
Art.-no. UPU1020

silentCOMFORT

The convenient mat for sturdy clicking installation of elastic floor coverings.




Adhesive top surface, floating installation, ultra-sturdy.
Impact sound reduction:
Up to 16 dB in the system with wineo 1000 for clicking in.
Art.-no. UCT1000

FEATURE STRIPS


When installed between the panels, the feature strips create outstanding effects from an authentic plank or tile look to optically extending the length of the room. Whether in discrete colours or sharp contrast, the feature strips can be glued with all elastic wineo flooring.

Uni-Design	2 mm	2.5 mm
Anthracite	AAN20DL	AAN25DL
Cream	ACR20DL	ACR25DL
Dark brown	ADB20DL	ADB25DL
Black	ASW20DL	ASW25DL
Silver grey	ASG20DL	ASG25DL




STAIR NOSING

For all wineo 1000 decors stair nosings are available:



TYPE A
Single-curved edge, without click connection in the front



TYPE C
Double-curved edge for wineo 1000 Connect



TYPE B
Single-curved edge with additional click connection in the front for installing a block stage



TYPE C
Double-curved edge for wineo 1000 Multi-Layer

SKIRTINGS

- new range available as of March 1st, 2019 (same decor: successively changeover from March 1st, 2019)
- decor matching MDF skirtings for all wineo floor coverings and universally usable skirtings MDF as well as plastic/aluminium
- installation heights from 60 mm to 100 mm
- plastic mounting clips included in the range of accessories; alternatively glue or tack
- self-adhesive corner elements for easy installation



PROFILES

- Comfort Profiles (self-adhesive profiles) for do-it-yourselfer
- Premium Profiles (screwable profiles) for professionals
- profile types for different applications: Transition-, Adjustment and End profiles, L-End profiles, expansion joint profile, Angle profiles and stair nosing profiles





THE BEST QUALITY FOR OVER 70 YEARS

For us, outstanding quality means more than an excellent product. As a family business in its 3rd generation we carry a high level of social and ecological responsibility. That's why we always provide you with the greatest possible level of transparency. And therefore even more safety.


- many quality controls from the initial mixing of the ingredients to the completion stage
- traceability of the exact time of production via a reverse-side overprint
- outstanding attributes regarding durability, maintenance and safety

MADE IN GERMANY



CE mark | CE mark for Multi-Layer

CE mark: The CE mark confirms that our product has been tested and meets all the EU-wide requirements for safety, health protection and environmental protection.



Österreichisches Umweltzeichen (Austrian eco-label)

The "Österreichisches Umweltzeichen" (Austrian eco-label) assesses products from quality, health-related and ecological standpoints. Basically, products can only be certified if they are harmless health-wise. The fulfilment of the criteria is checked every four years.



eco-bau Schweiz

Eco-Bau assesses the ecological aspects of building materials and services. It encompasses all of the significant environmental effects during the entire lifespan of the materials. The assessment is made on the basis of the following criteria: conservation of natural resources, energy for producing materials, solvent emissions, presence of environmentally and health-damaging components, emission of heavy metals and other damaging substances.

Mitglied der



DGNB

As a member of the German Sustainable Building Council (DGNB e.V.), wineo is committed to promoting environmental protection, health protection and socio-cultural objectives.



www.blauer-engel.de/uz120

www.blauer-engel.de/uz156

www.blauer-engel.de/uz176

"Blue Angel" (Blauer Engel)

"Blue Angel" (Blauer Engel): The "Blue Angel" guarantees that our products and services fulfil high requirements placed on environmental, health and usage properties. Criteria are compiled for each product group, which are checked every three to four years by the Federal Environment Agency.



TFI-TÜV PROFICERT | TFI-TÜV PROFICERT PREMIUM for Multi-Layer






The TFI (Textiles & Flooring Institute GmbH) and the TÜV Hessen evaluate products based on qualitative, health and ecological principals. Fundamentally, only products that are considered harmless to health can be certified.



Cradle to Cradle®

Cradle to Cradle® certification confirms the utilisation of environmentally safe, healthy and reusable materials (technical reutilisation) and the use of solar power or other regenerative sources of energy, together with responsible water stewardship and strategies adopted by a company to embrace its responsibility to society.

TECHNICAL CHARACTERISTICS

Collection	wineo 1000 wood	wineo 1000 wood XXL Multi-Layer	wineo 1000 stone		
Installation type	 Glue	 Click	 Click	 Glue	 Click
Utilisation class	23/32	23/32	23/32	23/32	23/32
Format	1298 × 200 mm	1295 × 195 mm	1845 × 237 mm	862 × 402 mm	859 × 397 mm
Product thickness	2.2 mm	5 mm	9 mm	2.2 mm	5 mm
Weight	3.4 kg / m ²	9 kg / m ²	8.7 kg / m ²	3.4 kg / m ²	9 kg / m ²
Planks or tiles / box	20 / 5.19 m ²	8 / 2.02 m ²	5 / 2.19 m ²	14 / 4.86 m ²	6 / 2.05 m ²
Boxes / pallet	48 / 249.12 m ²	48 / 96.96 m ²	48 / 105.12 m ²	50 / 243.00 m ²	48 / 98.40 m ²
Immunity to stains / Chemical resistance EN ISO 26987	very good resistance with regards to concentration and exposure time				
Reaction to fire EN 13501-1	C _s - s1				
Anti slip category DIN 51130	R9				
Light fastness EN ISO 105-B02	≥ 7				
Residual indentation EN ISO 24343-1	~ 0.05 mm				
Slip resistance EN 13893	μ ≥ 0.30 - DS				
Dimensional stability EN ISO 23999	~ 0.10 %	~ 0.10 %	not relevant	~ 0.10 %	~ 0.10 %
Underfloor heating	Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27 °C.				
Thermal resistance ISO 8302	~ 0.01 (m ² K)/W	~ 0.01 (m ² K)/W	~ 0.06 (m ² K)/W	~ 0.01 (m ² K)/W	~ 0.01 (m ² K)/W
Effect of a castor chair EN 425 / ISO 4918	Type W				
Impact sound reduction EN ISO 10140	~ 4 dB ~ 15 dB in the System with silentPREMIUM ~ 17 dB in the System with silentPLUS	~ 6 dB ~ 16 dB in the System with silentCOMFORT	~ 15 dB in the System with SoundPROTECT	~ 4 dB ~ 15 dB in the System with silentPREMIUM ~ 17 dB in the System with silentPLUS	~ 6 dB ~ 16 dB in the System with silentCOMFORT
anti-static properties EN 1815	≤ 2 kV				
Guarantee for private use according to Windmoller warranty conditions	30 years guarantee				



Utilisation class 23:
Heavy-duty use
in the domestic area



Utilisation class 32:
Normal use in the
commercial sector



Multi-Layer

wineo 1000 wood



1298 × 200 mm



1295 × 195 mm

wineo 1000 wood XXL

1845 × 237 mm

wineo 1000 stone



862 × 402 mm



859 × 397 mm

Windmüller GmbH

Nord-West-Ring 21

D-32832 Augustdorf

Tel.: +49 (0) 52 37 609 - 0

Fax: +49 (0) 52 37 609 - 309

info@wineo.de

www.wineo.de

Handed over by:

Product no. 20090837 | 02/2019

Member of

FEB **ERFMI.**

m
m
f
a

wineo