

ecolfit[®]

Single component, isocyanate and solvent-free, sililated polymer-based adhesive with a very low emission of volatile organic compound, for bonding all Listone Giordano[®] products.

Ecolfit is used for bonding on cementitious screeds, screeds made using a special hydraulic binder with normal setting and fast drying, old wooden floors, ceramic, marble, terrazzo, etc., anhydrite screeds. It is also suitable for underfloor heating and/or refreshing system.

Ecolfit is an adhesive:

- single-component, ready to use (no catalyst is required);
- with elasticity ideal for all multilayer parquet product of the Margaritelli Group;
- totally free of solvents and isocyanates;
- no risk to the health of Users of the parquet;
- 30% more yield compared with a two-component adhesive;

TECHNICAL DATA

consistency:	creamy paste
colour:	clear (beige)
density	1,65 ±0,05 gr/cm ³
dry solid content:	100%
application temperature range:	from +10°C (+50°F) to +30°C (+86°F)
consumption:	1,0 – 1,2 Kg/m ²
light foot traffic:	as possible after 12 hours
elongation at breakage:	100% (after 7 days at +23°C)

APPLICATION PROCEDURE

SUBFLOOR

The subfloor must be smooth, level, clean and with a compact surface so as to guarantee the best possible contact between the underside of the parquet and the subfloor itself.

To find out how to check the substrates, refer to the information sheet P08 - Listone Giordano installation and use guide.

PARQUET INSTALLATION

Spread the adhesive on the subfloor only using a suitably notched trowel and homogeneously (apply only the amount of Ecolfit which is to be covered within approximately 30 minutes under normal air conditions, T +23°C, R.H. 50%)

Lay the boards on top by interlocking them, if possible, using only your hands. Do not use other tools unless necessary and be sure they are covered with a material that ensures they will not harm the product. The planks should also be locked together, taking care not to allow adhesive into the joints.

It's forbidden the use of Puliplus[®] Listone Giordano or aggressive solvents to remove adhesive residues on oil finished hardwood floor especially if stained.

Keep out of the reach of children. Ensure good ventilation during and after use and drying. Do not eat, drink or smoke when using this product. In case of contact with skin or eyes, rinse immediately with plenty of water. Do not allow product to reach sewage system, water course or soil. Give only empty containers to recycling. Dried product residues may be disposed of as domestic waste. Product preservatives free. Methanol separates during hardening. Ensure constant ventilation when using this product. Ensure proper ventilation for several days after laying the flooring. Wear protective gloves. For information for allergic people, please call: +39 075 988 681.

The product contains: mineral fillers, binders, additives, drying agent, catalyst, stabilizer, pigments (VdI-RL 01 June 2018)

PRODUCT FOR PROFESSIONAL USE ONLY.



www.blauer-engel.de/liz113



Z-155.10-562

Exclusively manufactured for Listone Giordano by:

