

Blue Angel Environmental Information and Data Sheet Model: SG 3210DNw

Issued: 18th November 2021

EDP: 405857

1 General Specification						
Primary functions of the base unit						
Model : SG 3210DNw		🗌 Сору	🛛 Print	🗌 Fax	🗌 Scan	
		Monochror	ne	Colour		
Technology		Electropho	tographic	⊠ Inkjet/Gelje	 ⊠ Inkjet/Geljet Technology	
Print Speed Simplex, DIN-A4 pag according to ISO/IEC 24734	ges/min,	Monochrome: 13		Colour: 12	Colour: 12	
Maximum print speed		Monochrome: 29		Colour: 29	Colour: 29	
The system is designed for use	in the professio	nal/commercia	l sector.			
2 Technical Safety (Declaration	on of Conformity	y				
The system complies with the fo	llowing EU regu	lations as far	as they are ap	plicable and bears	s the CE mark	
 Radio Equipment Directive 2014/53/EU RoHS Directive 2011/65/EU ErP Directive 2009/125/EC 						
3 Environmental Labels						
www.blauer-engel.de/UZ219 . low energy consumption . low emissions and noise . durable The TEC value of the product based on the ENERGY STAR® Version 3.0 Test Method, and tested by the manufacturer, satisfies the program requirements. The requirements of the Blue Angel DE-UZ 219 eco-label were tested and met with the toner supplied and recommended						
by Ricoh. Further information on the Use and labelling of materia	-	i be louilu al. <u>Il</u>	.tps.//www.blat	<u>ler-eriger.de/eri</u>		
Paper	The device is suitable for processing recycled paper that complies with EN 12281:2002. We recommend using the machine in duplex mode (double-sided copy/print). The model is equipped with a duplex and N-up function:					
Toner/ Ink	Toner Ink/Gel					
Ames-Test	Negative (refer to Safety Data Sheet)					
Photo Conductor Unit	Organic Photo Conductor (OPC)					
Batteries	Mangandioxid Lithium Battery, free of lead, cadmium and mercury					
Flame Retardents	 No halogenated flame retardants are used in housing parts and other plastic parts over 25 g, especially not: Polybrominated Biphenyles (PBB), Polybrominated Biphenylether (PBDE) and Tetrabrombisphenol A (TBBPA). 					
Marking of Plastic Parts	All plastic parts >25g are marked in accordance with ISO 11469:2000 and ISO 1043.					
Proportion by weight of recycled plastic relative to total plastic (Post-consumer)	\square 0 - 1 % \square 10 - 15 % \square 1 - 5 % \square 15 - 20 % \square 5 - 10 % \square 20 - 25 %					



Legal requirements for recycling (WEEE)	The device fully complies with WEEE requirements.					
5 Yield of consumables						
Consumable	Description	EDP	Yield (A4)	Test procedure		
Print Cartridges	PRINT CARTRIDGE GC 51KH	405862	2.900	- ISO 24711		
	PRINT CARTRIDGE GC 51CH	405863	2.500			
	PRINT CARTRIDGE GC 51MH	405864	12.000			
	PRINT CARTRIDGE GC 51YH	405865	12.000			
Starter Toner			400	5%, A4		
Customer Replacement Units	INK COLLECTOR UNIT IC 51	405866	27.000	ISO 24711		
	The actual yield depends on the image size of paper used, the contents of the pri					

printed at one time, the type and size of paper used, the contents of the printed images, and environmental conditions such as temperature and humidity. Refer to the system's Operation Guide for more information on run times and the change intervals of consumables.

Note on handling the toner containers: Do not open the toner containers. When replacing them, please follow the instructions in the operating manual. Do not inhale any leaking toner as a result of improper handling, but wipe it off with a damp cloth. Avoid skin contact. If toner gets onto the skin, wash affected areas with plenty of cold water and soap. **Keep toner (old or new) out of the reach of children!**

Operational life: This machine is designed to have an operational life of 5 years or be good for 150,000 pages. The machine has an operational life of 5 years if used normally to produce up to 2,500 A4 prints a month. Exceeding these limits may reduce the operational life. The operational life also depends on the environment inshich the machine is used.

6 Warranty and spare parts

The guarantee for the devices corresponds to the legal regulations, as far as these are binding. All Ricoh distributors and subsidiaries offer all-in service contracts that go beyond the legal warranty. Please contact your local Ricoh office or distributor. Consumables and essential spare parts are available at least 5 years after the last unit in this series was sold.

7 Cleaning and Maintenance

Cleaning, maintenance and disposal activities may only be carried out by qualified personnel. Further information on cleaning and maintenance of the system can be found in the chapter "Maintenance and Specification" of the operating instructions.

8 Power Consumption	Determined according to DE-UZ 219 and ENERGY STAR® in delivery condition			
Operating Mode	Default Delay Time ¹⁾	Return Time ²⁾ (s)	Power Consumption (Watt	
Maximum Power Consumption			45	
Continuous Operation 13 ppm (15 min. printing time) monochrom			24	
Ready	0	0	6.55	
Sleep Mode	2 or activation by pressing the energy saver button	3	<1	
Off Mode	Switch	Switch		
TEC (Typical Electricity Consumption) reference value according to DE-UZ 219 0.16 kWh/Woche				
1) Default Delay Time: The time that	elapses after the end of the printing pro	ocess until the device autom	atically switches to an idle state.	

Default Delay Time: The time that elapses after the end of the printing process until the device automatically switches to an idle state.
 Return Time: The time it takes for the device to return from an energy-saving state to a print-ready state.

This product is designed to save energy costs. The system automatically reduces energy consumption when not used for a period of time (2 minutes). This mode is called Sleep Mode. From these states, the machine returns to standby printing in a short time (the return time listed above) when it receives a print or copy job. This allows you to save energy without limiting your productivity. With its return time, the system meets the high requirements of the Blue Angel, which attaches particular importance to user-friendliness in this respect.

The activation times for the sleep mode can be changed by the user in the range 1-60 minutes.

However, if the activation times are increased, this leads to higher energy consumption and thus to higher electricity costs. It is therefore recommended not to change the preset activation times.



When the main switch is actuated, there is still a low power consumption of max. 0.1 watts. Complete disconnection from the mains can be achieved by pulling the mains plug. Please observe the instructions in the operating instructions in order to prevent damage to the system and possible loss of data.

The device is designed so that it can be switched off at least twice a day.

Note on TEC (Typical Electricity Consumption). The aim of the TEC method is to determine the energy efficiency of hardcopy devices (copiers, printers, multifunction systems) and to make them comparable. The method determines the energy consumption of a product over a fixed period of time under normal operating conditions. The following usage cycle is assumed for the present system:

Per working day 13 print jobs with 6 pages, simplex at monochrome printing, (78 pages/day).

Hence, the energy consumption for a week in standard usage cycle according to ENER-GY STAR® version 3.0 (7-dayweek with 5 working days of 8 hours) is 0.16 kWh per week.

9 Noise Emissions						
	19 clause 3.5 printing mode					
9.1 According to DE-UZ 219 clause 3.5 printing mode Declared Sound Power Level (L _{WAd} in dB(A))BW 62.7				2.7		
Declared Sound Power Level (Lwad in dB(A)) Co 62.0						
	9 in combination with ISO 9296	6	I			
		Standby	Operation Monochr.	Operation Col.		
Sound Power Level (L _{WA} in	dB(A))	26.8	58,8 NA			
10 Chemical emissions d	10 Chemical emissions determined according to ISO/IEC 28360 with DE-UZ 219					
			Full Colour			
		Measured Value	Measured Value Reference value DE-UZ 219 (Blue Angel Mark)			
Pre-Operating Phase	TVOC [mg/h]	0,082	1			
Printing Phase (Sumo f Printing and Pre- operating phase)	TVOC [mg/h]	4,7	18			
	Benzene [mg/h]	0,0026	< 0,05			
	Styrene [mg/h]	0,015	1,8			
	Non identified VOC [mg/h]	0,11	0,9			
	Ozone [mg/h]		Not applicable			
	Dust [mg/h]	Not applicable				
Printing Phase	PER10 PW [Partikel/10min]		Not applicable			
LOD = Limit of detection, LOQ = Limit of qualification Blue Angel recommendation: New electronic devices generally emit volatile substances into the room air. For this reason, sufficient air exchange in the installation rooms and, if necessary, at the workplace should be ensured, especially in the first few days after the unit has been installed. The system is equipped with an ozone filter: Yes: Not applicable: ⊠ The system is equipped with dust filters:. Yes: Not applicable: ⊠ Further information on the filter change cycle can be found in the operating instructions						
11 Recycling						
Empty toner cartridges		Collection via Ricoh Resource Smart Return Program				
Full print cartridges	They can be handed in at any	Filled print cartridges should not be disposed of with household and commercial waste. They can be handed in at any RICOH branch and at any RICOH contractual partner.				
Waste ink	 ☐ Not applicable. ⊠ Please dispose according 	· · · · ·				
Batteries	Collection according to loc No battery used.	 ☑ Please dispose according to local legislation ☑ Collection according to local legislation. ☑ No battery used. 				
Spare parts		Return via Ricoh Resource Smart Return Program				
Devices	Used equipment is taken back and recycled in an environmentally friendly manner or - if this is no longer possible - recycled. Information about collection points for used RICOH products in your country can be obtained from your dealers or via the RICOH website:					

RICOH Europe



Contact: https://www.ricoh-europe.com I

Information on Ricoh's pan-European consumables collection system can be found on the following website: https://www.ricoh-return.com



12 Other

All information in this data sheet is based on the current state of our knowledge. They do not represent any assurance of the properties of the product described within the meaning of the statutory warranty regulations.