

Product Additional moisture protection, should be installed under all insulation underlays without integrated moisture protection.

Product composition Polyethylene and copolymers/recyclates

Advantages

- Moisture protection
- Suitable for installation over underfloor heating
- Easy to install

Installation

- Overlap seams at approx. 30 cm
- Easy and dust-free to cut to size with a general-purpose cutter (carpet knife)

Technical data



www.blauer-engel.de/uz30a

Thickness	0.2 mm (+/- 25 %)
Mass density	approx. 0.92 g/cm ³
Tensile strength, longitudinal	>/= 16 N/mm ²
Tensile strength, transverse	>/= 15 N/mm ²
Elongation at break, longitudinal	>/= 250 %
Elongation at break, transverse	>/= 250 %
Dart drop	>/= 1 g/μm
SD value	≥ 90 m
Suitable for underfloor heating	Yes

Weight per unit area	156,4 g/m ² (+/- 5 %)
Dimensions	13 x 2 m
Roll coverage	26 m ²
Content/pallet	2158 m ² = 83 rolls
Packaging	Individual rolls wrapped in foil with guide lines 83 rolls on a Euro pallet

This technical information is for your guidance and support and is based on our most up-to-date knowledge. It makes no representation or warranty, express or implied, as to any specific properties of the described product within the meaning of the statutory warranty regulations.