



## Web Offset Heatset

### MG 1500

**MG 1500** ink series can be used universally on a wide range of different paper grades. The spectrum of substrates that can be printed with ranges from newsprint and SC papers to LWC qualities and other coated substrates. **MG 1500** is characterised by excellent printing stability and outstanding running properties in production printing.

The tack of **MG 1500** is set comparatively low so that even papers that are sensitive to picking can be processed without any problems. Due to the slightly higher tack value compared to **UNI 500**, **MG 1500** prints with slightly sharper dots and more contrast, but is also a little more sensitive to blanket and plate build-up.

**MG 1500** ink series fulfils all requirements for the award criteria of the new 'Blue Angel for printing inks, inks and toners for paper and cardboard on professional printing machines' (DE-UZ 237, July 2024 edition) up to a minimum paper weight of 40 g/m<sup>2</sup> and the 'Blue Angel for printed products' (DE-UZ 195, January 2021 edition).

#### Special properties

- low dot gain and high contrast
- Fast drying
- High gloss
- Excellent runability
- Excellent transfer and colour acceptance behaviour (trapping)
- Colour locations according to DIN ISO 2846-1 and ISO 12647-2
- Optimum print stability
- Formulated with low-aromatic mineral oils

Schuite & Schuite Druckfarben GmbH  
Wolff-Knippenberg-Straße 1, 99334 Amt Wachsenburg OT Ichtershausen  
Phone: +49 (0) 3628 5815 0, Website: [www.s-s-inks.de](http://www.s-s-inks.de)