

PRODUCT INFORMATION

TECTROL TERRA BETO 450 PLUS

Environmentally friendly universal release agent,
free of mineral oil and solvents

TECTROL TERRA BETO 450 PLUS is a readily biodegradable, label-free release agent based on renewable raw materials, which fulfils the environmental criteria according to RAL-UZ 178.

TECTROL TERRA BETO 450 PLUS is a non-water-miscible release agent that can be used undiluted in construction and civil engineering for non-absorbent or low-absorbent formwork (phenolic resin formwork skins), as well as plastic and plastic-coated formwork. It is not sensitive to frost and can therefore be used in any weather.

GISCODE: BTM 10

Benefit	Use
Solvent-free	Safety in the workplace
Biodegradable	Protects the environment
Excellent concrete surface	Clean concrete work without additional effort
Product made from renewable raw material	Reduced impact on the climate
Free of hydrocarbons	Health risks are reduced



PRODUCT INFORMATION

TECTROL

TERRA BETO 450 PLUS

Environmentally friendly universal release agent,
free of mineral oil and solvents

Specifications (average values)

Specific value	Typical value	Test method
kinematic viscosity at 20°C	14.5 mm ² /s	ASTM D 7042
density at 15°C	0.89 g/ml	DIN 51 757
pourpoint	-12 °C	DIN ISO 3016
flash point	200 °C	DIN ISO 2592
Colour	clear	DIN ISO 2049
GISCODE	BTM 10	

Recommendations for use

The product is applied as supplied by spraying,
brushing or rolling.
Ready to use.



Issuing body:
BayWa AG, München
Energie
Technical Purchasing Lubricants
Telephone: +49 89 9222-2039

All data and information is provided based on our current level of
knowledge as of: 29.02.24
Any previous versions are invalid. Subject to change without notice.
For further details and information, please visit www.tectrol.de.