



TECHNICAL DATA SHEET

Divinol SYN BE Plus

A solvent-free, non-water-miscible release agent for all common types of moulds, awarded with the Blue Angel (RAL-UZ 178) and the EU-Ecolabel

PRODUCT DESCRIPTION

- + non-watermiscible release agent
- + solvent-free, mineral oil free
- + based on renewable resources
- + no discolouration of the concrete surface
- + economic consumption
- + easily biodegradable
- + free from labeling



www.blauer-engel.de/uz178

CHARACTERISTICS

Colour / DIN ISO 2049	1.0
Appearance	clear
Density/15°C / DIN EN ISO 12185	890 kg/m ³
Viscosity/20°C / ASTM D 7042	14.5 mm ² /s
Flash point (Cleveland) / DIN ISO 2592	> 160 °C

31860

07/2020-31860-5

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.



TECHNICAL DATA SHEET

Divinol SYN BE Plus

A solvent-free, non-water-miscible release agent for all common types of moulds, awarded with the Blue Angel (RAL-UZ 178) and the EU-Ecolabel

Pour point / ASTM D 7346	-12 °C
Operating temperature range	0 °C - 60 °C
Giscode	BTM 10
Water hazardous class	1

APPROVAL

Awarded with the environmental label "Blue Angel" RAL-UZ 178 and the EU Ecolabel

APPLICATION

Divinol SYN BE Plus can be used for all common types of formwork in civil engineering: for non-absorbent or less absorbent formwork (phenolic resin formwork facing) as well as for all-plastic and plastic coated formworks. Use on heated formworks is possible.

The product is very suitable as mixer protection.

Divinol SYN BE Plus be applied in the state at time of delivery by spraying, brushing or rolling without any problems. If used properly **Divinol SYN BE Plus** does not influence negatively the subsequent treatment of the concrete surface (plastering, ceramics, wallpaper, paint).

STORAGE

Divinol SYN BE Plus is not sensitive to frost and can be applied in all kinds of weather conditions.

Benefit from our service, we will gladly advise you and develop individual application recommendations for your process. Please also note the material safety data sheet.

31860

07/2020-31860-5

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.