

DESCRIPTION				
Total Thickness	EN ISO 24346	mm	2	
Weight	EN ISO 23997	g/m <sup>2</sup>	3480	
Size	EN ISO 24342	mm	457x914	184x1219
Number of planks /tiles and sqm per box	-	-	9 / 3.76m <sup>2</sup>	15 / 3.36m <sup>2</sup>
CLASSIFICATION				
Norm/Product Specification	-	-	EN ISO 19322	
European Classification	EN ISO 10874	class	34 - 43	
Fire Rating	EN 13 501-1	class	Bfl-s1	
Static Electrical Propensity	EN 1815	kV	< 2	
Slip Resistance Wet	DIN 51 130	class	R10	
PERFORMANCES				
Wear Resistance	EN 660.2	mm <sup>3</sup>	< 2.0	
Room Impact	NF S 31074	dB	77	
Impact sound insulation	EN ISO 717-2	dB	4	
Dimensional stability (norm)	EN ISO 23999	%	≤ 0.25	
Dimensional stability (average measured value)	-	%	≤ 0.10	
Residual Indentation	EN ISO 24343-1	mm	≤ 0.10	
Castor chair test	ISO 4918	-	OK	
Thermal Conductivity	EN ISO 10456	W/(m.K)	0.25	
Colour Fastness	EN 20 105 - B02	degree	≥ 6	
Surface Treatment	-	-	PUR+ MATT	
Chemical Products Resistance	EN ISO 26987		OK	
ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days	ISO 16000-6	µg/ m3	< 10	
CE MARKING				
	EN 14041			
				