

Kiehl-Legnodur-satina

Matt 1-component permanent coating

- ▲ Varnish-like, matt-drying, plasticiser-free polyurethane emulsion polish
- ▲ Outstanding film-forming properties
- ▲ Hard-wearing, easy to clean protective film
- ▲ Maintenance of the coating after dry cleaning
- ▲ The film cannot be removed by wet stripping
- ▲ Extremely good water resistance



Area of application

On real wood surfaces, which have been coated with wood oils or sealants. Also suitable for resilient floor surfaces and screed flooring which can be coated.

Application

Please test on a small inconspicuous spot before first application. The surfaces must be clean, release-agent free and properly prepared to ensure faultless adhesion and appearance. Shake well before use. Do not let the product dry on the mop. Close canister immediately after use. Avoid draughts during use and drying.

Preparation of the surface:

Dry clean parquet surfaces before coating (use Kiehl-Legno Pad). Resilient floor coverings must be stripped (Veroclean, 3 L in 8 L of water). Resilient floorings already coated with Kiehl-Legnodur must be dry cleaned using a Kiehl-Legno Pad. Accruing dust must be removed.

Coating:

Depending on the absorbency of the surface, 1–2 layers at intervals of approx. 90 minutes. After preparing the surfaces, apply a thin coat of undiluted product to the clean floor using a flat mop or waxer. Consumption: 30.0 ml/m² per application.

Clean tools with water.



Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only! Protect from frost. Keep out of the reach of children. Not suitable for paint spraying. Use P2 dust filter for grinding. When using do not eat, drink or smoke. In case of contact with eyes or skin, immediately and thoroughly rinse with water. Ensure good ventilation during use and drying. Clean utensils immediately after use with soap and water. Do not empty into drains, aquatic environment or earth. Make sure that containers are completely empty for recycling. Liquid paint leftovers should be returned to a collection facility for paint residues.

Ingredients (according to 648/2004/EC)

Synthetic dispersions, free from metal salts, polyethylene waxes, water-soluble solvents, preservatives (Benz-, Methyl-, Methylchloroisothiazolinone). pH value (concentrate): approx. 8

Classification

Classification (in concentrate): EUH208 Contains Benz-, Methyl-, Methylchloroisothiazolinone. May produce an allergic reaction.

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j220805	Carton of 2 x 5 L PCR canisters	56