WorkForce Enterprise WF-C21000 D4TW

DATASHEET / BROCHURE









Small-in-One with individual inks, user-friendly Wi-Fi for multiple users and mobile printing.

The Epson Expression Home XP-215 comes with Epson Connect¹, offering greater flexibility and freedom. It allows you to quickly and easily print documents and photos over Wi-Fi from smartphones and tablet PCs. You can also print from anywhere in the world by emailing documents and photos directly to the printer.

Cloud Support

The automatic Wi-Fi set-up² makes configuring laptops and computers to print and scan wirelessly extremely easy. You don't need to know your network settings, as the XP-215 automatically finds the relevant connection settings in order to configure itself.

Automatic Wi-Fi set-up²

Cartridge sizes

KEY FEATURES

- Faster performance
 Fast FCOT of 4.9 seconds and print speeds of up to 100ppm
- High capacity ink yield
 Users can print up to 100,000 pages in mono or 50,000 in colour without changing the ink supplies¹
- Improved finishing capability
 Robust finishing such as booklet finisher and hole punch options
- Powerful scanning capability
 Thin paper support and improved quality of scanning
- Works with Epson Remote Services
 Cloud based, advanced diagnosis of
 Epson printers and MFPs
- Legal Statement
 Complies with The UK Product Security
 and Telecommunications Infrastructure
 (Product Security) requirements. Epson
 will provide security updates for 7 years
 from purchase



PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method PrecisionCore™ Micro TFP printhead Nozzle Configuration 8,676 Nozzles Black, 8,676 Nozzles per Color

Minimum Droplet Size 3.5 pl

DURABrite™ Pro Ink Technology Category Office Departmental All-in-One Functions Print, Scan, Copy

PRINT

First Page Out Monochrome 4.9 Seconds, Colour 4.9 Seconds Printing Speed ISO/IEC 24734 100 pages/min Monochrome, 100 pages/min Colour **Duplex Printing Speed** 100 A4 Pages/min Monochrome, 100 A4 Pages/min Colour

ISO/IEC 24734

Printing Speed ISO/IEC 24734 54 pages/min Monochrome, 54 pages/min Colour

(A3)

Duplex Printing Speed 36.6 A4 Pages/min Monochrome, 36.6 A4 Pages/min Colour

ISO/IEC 24734 (A3)

Maximum Printing Speed 100 pages/min Monochrome (plain paper 75 g/m²), 100 pages/min Colour (plain paper 75 g/m²)

Printing Resolution 600 x 2,400 DPI Printing Volume 400,000 pages per month

The maximum number of printed pages per month based on the performance capabilities of

the printer, including ISO rated print speeds and paper handling capabilities.

Recommended Duty Cycle 8,000 - 100,000 pages per month Colours Black, Cvan, Yellow, Magenta

For detailed information on printing speeds please visit http://www.epson.eu/testing.

SCAN

Double-sided scanning

60 ipm (Monochrome, Single-sided, 300 dpi, ADF); 110 ipm (Monochrome, Double-sided, Scanning Speed

300 dpi, ADF); 60 ipm (Colour, Single-sided, 300 dpi, ADF); 110 ipm (Colour, Double-sided,

300 dpi, ADF);

Optical Resolution 600 DPI x 600 DPI (Horizontal x Vertical) Optical Resolution (ADF) 600 DPI x 600 DPI (Horizontal x Vertical)

Scan to Email, Scan to FTP, Scan to USB, Computer (Epson Document Capture Pro), USB Advanced document

integration Memory Device / Card

BMP, JPEG, TIFF, multi-TIFF, PDF, PNG **Output formats**

Scanner type Contact image sensor (CIS)

Optical Resolution 600 DPI x 600 DPI (Horizontal x Vertical)

Type of fax Walk-up black and white and colour fax capability

Fax Transmission Speed Up to 33.6kbps / Approx. 3 sec/page

CCITU/ITU Group3 fax with Error Correction Mode Error correction mode

Fax speed dials (max) 2,000 names and numbers

Page memory Up to 550 pages/ 6MB (ITU-T No. 1 chart)

Fax Functions PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Fax to Folder, Address Book, Fax

Preview, Polling Reception

WorkForce Enterprise WF-C21000 D4TW

WHAT'S IN THE BOX

- Information sheet
- Power cable
- User guide



PRODUCT SPECIFICATIONS

WorkForce Enterprise WF-C21000 D4TW

COPY

Copy Speed Up to 100 ipm Black, Up to 100 ipm Colour

*Simplex ADF 600 x 600 dpi (ISO/ IEC 24735)

Copy resolution (dpi) 600 x 1200
Reduction / Enlargement 25 % - 400 %
Maximum number of copies 9,999
Maximum Copy Size A3

CONNECTIVITY

Network Printing Protocols IPP, LDP, Port 9100, WSD

Network Management SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping

Protocols

Network Protocol IPv4, IPv6

Interfaces 10 Base-T, Ethernet interface (100 Base-TX / 10 Base-T), Ethernet 1000, Ethernet Interface

(1000 Base-T/ 100-Base TX/ 10-Base-T), Wireless LAN IEEE 802.11a/b/g/n, Wi-Fi Direct, USB

1.0-A, USB 2.0-A, USB 3.0 Type B

WLAN Security WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES)

Network Protocol TCP/IPv4, TCP/IPv6, TCP, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL/TLS

PAPER / MEDIA HANDLING

Paper Formats A3 (29.7x42.0 cm), A4 (21.0x29.7 cm), Postcard, A3+, A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B4,

B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope), Executive, Letter, Legal,

HLT, No. 10 (Envelope), User defined

Automatic Document Feed 150 pages

Compatible Paper Weight 60 - 350g/m²

Duplex Yes (A4/A3, plain paper)

Standard Paper input 2,350 Sheets Standard, 150 Sheets MP tray, 550 Sheets paper tray

Output Tray Capacity 550 Sheets
Maximum paper input 5,350
Number of paper trays 4

PAPER FEED MPT

Custom sizes

Paper Input Name MPT

Paper Formats A3+, A3, A4, A5, A6, B4, B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope),

Letter, 20 x 25 cm, HLT, User defined, SRA3 Min 55x 330 mm to Max 127x 1,200 mm

Compatible paper weight 60 g/m² - 350 g/m²

Paper Capacity 1 150 80gsm

Media type Plain Paper, Recycled Paper, Colour Paper, Letterhead

PAPER FEED C1

Paper Input Name C1

Paper Formats A3, A4, A5, B4, B5, Letter, HLT, Executive
Custom sizes Min 140x 297 mm to Max 182x 432 mm

Compatible paper weight 60 g/m² - 160 g/m²
Paper Capacity 1 550 80gsm

Media type Plain Paper, Recycled Paper, Colour Paper, Letterhead

PAPER FEED C2-C4

Paper Input Name C2-C4

 Paper Formats
 A3, A4, A5, B4, B5, Letter, HLT

 Custom sizes
 Min 140x 297 mm to Max 182x 432 mm

 $\begin{array}{ll} \mbox{Compatible paper weight} & \mbox{60 g/m}^2 - 160 \mbox{ g/m}^2 \\ \mbox{Paper Capacity 1} & \mbox{550 80gsm} \end{array}$

Media type Plain Paper, Recycled Paper, Colour Paper, Letterhead

PAPER FEED LCT

 Paper Input Name
 LCT

 Paper Formats
 A4, Letter

 Compatible paper weight
 60 g/m² - 160 g/m²

 Paper Capacity 1
 3,000 80gsm

Media type Plain Paper, Recycled Paper, Colour Paper, Letterhead



PRODUCT SPECIFICATIONS

PAPER FEED DUPLEX

Paper Input Name Duplex

Compatible paper weight 60 g/m² - 160 g/m²

GENERAL

Energy Use 170 Watt (standalone copying, ISO/IEC 24712 pattern), 1.1 Watt (sleep mode), 76 Watt (Ready),

0.1 Watt (Power off), TEC 0.4 kWh/week

Supply Voltage AC 100 V - 240 V. 50 Hz - 60 Hz

Product dimensions 674 x 757 x 1,243 mm (Width x Depth x Height)

177.1 ka Product weight

Compatible Operating Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X Systems

10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 11, Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista

(32/64 bit), Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or

later, XP Professional x64 Edition SP2

Operation: 7.5 B (A) Sound Power Noise Operation: 60 dB (A) 220V, 240V Power supply

ADDITIONAL FEATURES

Features Touchscreen

Type: Color, Touchscreen, Diagonal: 22.7 cm

Media Handling Duplex (A4/A3, plain paper)

Security Functions Limit access function with Epson Web Config, Secure confidential printing with PIN code

release, LDAP Address Book, IPsec, IEEE802.1x, SSL (Server authentication), Panel Admin

Mode

HDD HDD, Encrypted, 320GB

OTHER FEATURES

PCL5c, PCL6, PostScript 3, PDF 1.7, ESC/P, ESC/P-R, PCL5e, ESC/Page, ESC/Page-Colour Emulations

SUPPLIES

WorkForce Enterprise WF-C21000 Black Ink	C13T02Y100	50,000 pages
 WorkForce Enterprise WF-C21000 Cyan Ink 	C13T02Y200	50,000 pages
 WorkForce Enterprise WF-C21000 Magenta Ink 	C13T02Y300	50,000 pages
WorkForce Enterprise WF-C21000 Yellow Ink	C13T02Y400	50,000 pages
Maintenance box	C13T671300	

OPTIONAL ACCESSORIES

Cassette Lock

C12C933231

• Super G3/G3 Fax Board

C12C934491

LOGISTICS INFORMATION

sкu	C11CH88401BY
EAN code	8715946677064
Country of Origin	Indonesia
Layer	1 Units
Layer Block	1 Units



For more information please contact:


Home users: 0343 90 37766 Business users*: 0871 42 37766 Republic of Ireland: 01 436 7742

Or visit us at https://www.epson.co.uk/contactus * 10p per minute plus network extras.

www.epson.co.uk www.epson.ie

WorkForce Enterprise WF-C21000 D4TW

INK YIELD DATA



Approx, page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit http://www.epson.eu/pageyield

- 1. ¹Approx. page yield with the WF-C20600. Actual yield will vary depending on images printed and usage conditions. For more information visit
- www.epson.eu/pageyield.
 2. ²Fax optional in certain territories at an additional cost. Please contact your local Epson office for more information.
- 3. ³Approx. based on internal testing; may vary depending on the number of copies selected, the output environment, as well as the settings for size, orientation, position of paper.

