

SCHÖNOX® TEX XTREME

Very low emission textile covering dispersion adhesive

suitable for gluing for all kind of common textile coverings, also e.g. needlefelt on absorbent floors. Rapid increase of adhesion force due to secure technology. General construction regulation approval. Emission Tested by DIBt construction principles.

Extreme tack. Extreme increase of adhesion force.



Product characteristics

- approved by the building authorities
- Emission tested building product according to DIBt-principles - approval no.: Z-155.20-411
- EMICODE EC 1^{PLUS}: very low emission
- RAL UZ 113: Environment-friendly, because very low-emission
- high safety with intensive use (e.g. hospitals, airports, shopping malls)
- extreme tack
- extreme increase of adhesion force
- counteracts effective to seam shrinkage
- low odour
- easy to apply
- short waiting time
- strong stringiness
- suitable for wet adhesion
- suitable for castor wheels in accordance with EN 12 529
- suitable for application on subfloor heating systems
- suitable for shampooing according to RAL 991 A2
- solvent-free according to TRGS 610
- for interior use
- suitable on all SCHÖNOX levelling compounds

Applications

SCHÖNOX TEX XTREME is suitable for bonding of:

- single or multi-layer needlefelt
- textile coverings with
 - synthetic secondary backing or jute backing
 - filling compound-free backing constructions
 - suitable non-woven backing
- natural fibre coverings with backing such as coir and sisal on suitable absorbent substrates in living- and business areas (interior).

Requirements of substrate

- Adequate strength, load bearing capacity, dimensional stability and permanent dryness.
- Free of residues which reduce adhesion, e.g. dust, dirt, oil, fat and loose particles.
- Sound, even surfaces with absorbency level appropriate to use are achieved by using SCHÖNOX levelling compounds, layer thickness for vapor proof coverings as well as on non absorbent substrates at least 2 mm.
- In order to receive the substrate requirements of the specific coverings, refer to the technical product information of the coverings manufacturer.
- The requirements of the relevant valid standards, guidelines and data sheets apply.

Recommended method of working

- SCHÖNOX TEX XTREME is a very low emission dispersion adhesive and should be stirred before use.
- Coverings to be laid with SCHÖNOX TEX XTREME should be conditioned, unstressed and in a flat position.
- Spread the adhesive evenly on the substrate using a notched trowel. Avoid lumps of adhesive.
- Recommended trowel size:
 - Textile coverings: TKB B1/B2
- The right amount of adhesive is determined by the backing of the covering. Ensure that there is adequate wetting.
- After laying without bubbles, rub down the covering and after a waiting time rub again or roll it.
- Laying stages:
 - "wet phase": adhesive applied does not yet display any stringiness.
- Clean tools in water immediately after use.

Technical data

- Basis: synthetic resin dispersion with bonding additives
- Color: beige
- Density: 1,35 kg/l
- Storage temperature: not below + 5 °C
- Application temperature: not below + 15 °C floor temperature
- Material consumption:
 - notched trowel TKB A2: 350 g/m²
 - notched trowel TKB B1: 400 g/m²
- Waiting time: none
- Open time: approx. 20 min
- Drying time: approx. 24 hours
- Final strength: after approx. 72 hours

All values are approximate, are subject to local climatic fluctuations and vary according to the absorbency of the substrates and the applicator device.



SCHÖNOX® TEX XTREME

- Direct securing to old adhesive residues can lead to interactions and thus to unpleasant smells.

Packaging

- 14,0 kg plastic pail

Storage

- Store SCHÖNOX TEX XTREME in cool, dry, frost-free conditions.
- Storage life of 1 year (in closed packaging).
- Opened packages should be closed immediately and used up as soon as possible.
- Remove any skin that has formed, do not stir in.

Disposal

- Empty packaging completely and dispose of in accordance with regulations
- For the disposal of product residues, waste water and containers with adherent product residues please follow the local governmental regulations.
- Do not empty into drains, waters or soil.

EMICODE

- EC 1^{PLUS}: very low emission

GISCODE

- D1 - solvent-free dispersion adhesives and primers

EPD - Self-declaration

Sika Deutschland GmbH declares that the product fulfills the criteria for dispersion based products, solvent-free.

ENVIRONMENTAL PRODUCT DECLARATION

acc. to ISO 14025 and EN 15804

Owner of declaration

Deutsche Bauchemie e.V.
Industrieverband Klebstoffe e.V.
Verband der deutschen Lack- und Druckfarbenindustrie e.V.

FEICA - Association of the European Adhesive and Sealant Industry

Editor

Institut für Bauen und Umwelt e.V. (IBU)

Program owner

Institut für Bauen und Umwelt e.V. (IBU)

Number of declaration

EPD-FEI-20160086-IBG1-EN

Date of issue

29.08.2016

Valid until

28.08.2021

Hazard class

- does not apply

Instructions

- Clean tools immediately in water with low surface tension.
- Wipe impurities immediately from the covering surface and remove residual skin using a suitable cleaning agent (e.g. SCHÖNOX FIX CLEAN).
- Apply caps to protect the surface of the covering at the earliest after 72 hours.
- Follow the covering manufacturer's laying instructions. If in doubt, we recommend testing a small area.
- Composition:
 - Polyacrylate dispersions
 - Mineral fillers
 - Additives
 - Preservatives based on Benz-/Methylisothiazolinone
- Informations for allergic persons call +49 2547 910-0.
- Insure a good ventilation during application and drying.
- Avoid eating, drinking and smoking while working with the product.
- In case of contact with eyes or skin, rinse immediately with plenty of water.
- Keep out of the reach of children.

The applicable recommendations, guidelines, DIN regulations and safety data sheets are to be observed, together with the recognised architectural and engineering regulations. We guarantee that our products leave the factory in perfect condition. While our recommendations for use are based on tests and practical experience, they can only provide general guidance without any assurance as to product characteristics, since we have no influence over the conditions on site, the execution of the work or the method of processing. This product data sheet supersedes all previous editions.



The Sika management system is certified to ISO 9001 and 14001 by SQS

Sika Deutschland GmbH

Subsidiary Rosendahl

P.O. Box 11 40

D-48713 Rosendahl / Germany

Phone +49 (0) 2547-910-0

Fax +49 (0) 2547-910-101

E-mail: info@schoenox.de

www.schoenox.com